

Principles of Knowledge Representation and Reasoning

Semantic Networks and Description Logics IV:
Description Logics – Algorithms

Bernhard Nebel, Felix Lindner, and Thorsten Engesser

November 30, 2015

Principles of Knowledge Representation and Reasoning

Semantic Networks and Description Logics IV:
Description Logics – Algorithms

Bernhard Nebel, Felix Lindner, and Thorsten Engesser

November 30, 2015

1 Motivation

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Literature

Reasoning problems & algorithms

Reasoning problems:

- **Satisfiability** or **subsumption** of concept descriptions
- **Satisfiability** or **instance relation** in ABoxes

Solving techniques presented in this chapter:

- **Structural subsumption algorithms**
 - **Normalization** of concept descriptions and **structural comparison**
 - very fast, but can only be used for small DLs
- **Tableau algorithms**
 - Similar to modal tableau methods
 - Often the method of choice

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Literature

2 Structural Subsumption Algorithms

- Idea
- Example
- Algorithm
- Soundness
- Completeness
- Generalizations
- ABox Reasoning

Motivation

Structural
Subsumption
Algorithms

Idea

Example

Algorithm

Soundness

Completeness

Generalizations

ABox Reasoning

Tableau
Subsumption
Method

Literature

Structural subsumption algorithms

In what follows we consider the rather **small** logic \mathcal{FL}^- :

- $C \sqcap D$
- $\forall r.C$
- $\exists r$ (simple existential quantification)

To solve the subsumption problem for this logic we apply the following idea:

- 1 In the conjunction, collect all **universally quantified expressions** (also called **value restrictions**) with the same role and build **complex value restriction**:

$$\forall r.C \sqcap \forall r.D \rightarrow \forall r.(C \sqcap D).$$

- 2 Compare all conjuncts with each other.
For each conjunct in the subsuming concept there should be a **corresponding one** in the subsumed one.

Motivation

Structural
Subsumption
Algorithms

Idea

Example

Algorithm

Soundness

Completeness

Generalizations

ABox Reasoning

Tableau
Subsumption
Method

Literature

Example

Example

$$D = \text{Human} \sqcap \exists \text{has-child} \sqcap \forall \text{has-child. Human} \sqcap \\ \forall \text{has-child.} \exists \text{has-child}$$
$$C = \text{Human} \sqcap \text{Female} \sqcap \exists \text{has-child} \sqcap \\ \forall \text{has-child. (Human} \sqcap \text{Female} \sqcap \exists \text{has-child)}$$

Check: $C \sqsubseteq D$

1 **Collect** value restrictions in D :

... $\forall \text{has-child. (Human} \sqcap \exists \text{has-child)}$

2 **Compare**:

1 For Human in D , we have Human in C .

2 For $\exists \text{has-child}$ in D , we have $\exists \text{has-child}$ in C .

3 For $\forall \text{has-child. (...)}$ in D , we have Human and $\exists \text{has-child}$ in C .

\rightsquigarrow C is subsumed by D !

Motivation

Structural
Subsumption
Algorithms

Idea

Example

Algorithm

Soundness

Completeness

Generalizations

ABox Reasoning

Tableau
Subsumption
Method

Literature

Subsumption algorithm

SUB(C, D) algorithm:

- 1 Reorder terms (using **commutativity**, **associativity** and **value restriction law**):

$$C = \bigwedge A_i \cap \bigwedge \exists r_j \cap \bigwedge \forall r_k : C_k$$

$$D = \bigwedge B_l \cap \bigwedge \exists s_m \cap \bigwedge \forall s_n : D_n$$

- 2 For each B_l in D , is there an A_i in C with $A_i = B_l$?
- 3 For each $\exists s_m$ in D , is there an $\exists r_j$ in C with $s_m = r_j$?
- 4 For each $\forall s_n : D_n$ in D , is there a $\forall r_k : C_k$ in C such that $s_n = r_k$ and $C_k \sqsubseteq D_n$ (i.e., check SUB(C_k, D_n))?

$\rightsquigarrow C \sqsubseteq D$ iff all questions are answered positively.

Motivation

Structural
Subsumption
Algorithms

Idea

Example

Algorithm

Soundness

Completeness

Generalizations

ABox Reasoning

Tableau
Subsumption
Method

Literature

Soundness

Theorem (Soundness)

$$SUB(C, D) \Rightarrow C \sqsubseteq D$$

Proof sketch.

Reordering of terms **step (1)**:

1 Commutativity and associativity are trivial

2 Value restriction law. We show: $(\forall r.(C \sqcap D))^{\mathcal{I}} = (\forall r.C \sqcap \forall r.D)^{\mathcal{I}}$

Assume $d \in (\forall r.(C \sqcap D))^{\mathcal{I}}$.

If there is no $e \in \mathcal{D}$ with $(d, e) \in r^{\mathcal{I}}$ it follows trivially that

$$d \in (\forall r.C \sqcap \forall r.D)^{\mathcal{I}}.$$

If there is an $e \in \mathcal{D}$ with $(d, e) \in r^{\mathcal{I}}$ it follows $e \in (C \sqcap D)^{\mathcal{I}} = C^{\mathcal{I}} \cap D^{\mathcal{I}}$.

Since e is arbitrary, we have $d \in (\forall r.C)^{\mathcal{I}}$ and $d \in (\forall r.D)^{\mathcal{I}}$,

i.e., $(\forall r.(C \sqcap D))^{\mathcal{I}} \subseteq (\forall r.C \sqcap \forall r.D)^{\mathcal{I}}$.

The other direction is similar.

Steps **(2+3+4)**: Induction on the nesting depth of \forall -expressions.

Completeness

Theorem (Completeness)

$$C \sqsubseteq D \Rightarrow \text{SUB}(C, D).$$

Proof idea.

One shows the contrapositive:

$$\neg \text{SUB}(C, D) \Rightarrow C \not\sqsubseteq D$$

Idea: If one of the rules leads to a negative answer, we use this to construct an interpretation with a special element d such that

$$d \in C^{\mathcal{I}}, \text{ but } d \notin D^{\mathcal{I}}.$$



Motivation

Structural
Subsumption
Algorithms

Idea

Example

Algorithm

Soundness

Completeness

Generalizations

ABox Reasoning

Tableau
Subsumption
Method

Literature

Generalizing the algorithm

Extensions of \mathcal{FL}^- by

- $\neg A$ (atomic negation),
- $(\leq nr), (\geq nr)$ (cardinality restrictions),
- $r \circ s$ (role composition)

do not lead to any problems.

However: If we use full existential restrictions, then it is very unlikely that we can come up with a **simple** structural subsumption algorithm – having the same flavor as the one above.

More precisely: There is (most probably) no algorithm that uses polynomially many reorderings and simplifications and allows for a simple structural comparison.

Reason: Subsumption for $\mathcal{FL}^- + \exists r.C$ is NP-hard (Nutt).

Motivation

Structural
Subsumption
Algorithms

Idea

Example

Algorithm

Soundness

Completeness

Generalizations

ABox Reasoning

Tableau
Subsumption
Method

Literature

Idea: Abstraction + classification

- **Complete** ABox by propagating value restrictions to role fillers.
- Compute for each object its **most specialized concepts**.
- These can then be handled using the ordinary subsumption algorithm.

Motivation

Structural
Subsumption
Algorithms

Idea

Example

Algorithm

Soundness

Completeness

Generalizations

ABox Reasoning

Tableau
Subsumption
Method

Literature

3 Tableau Subsumption Method

- Example
- Reductions: Unfolding & Unsatisfiability
- Model Construction
- Equivalences & NNF
- Constraint Systems
- Transforming Constraint Systems
- Invariances
- Soundness and Completeness
- Space Complexity
- ABox Reasoning

Motivation

Structural
Subsumption
Algorithms

**Tableau
Subsumption
Method**

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Tableau method

Logic \mathcal{ALC} :

- $C \sqcap D$
- $C \sqcup D$
- $\neg C$
- $\forall r.C$
- $\exists r.C$

Idea: Decide (un-)satisfiability of a concept description C by trying to **systematically construct** a model for C .

If that is successful, C is satisfiable. Otherwise, C is unsatisfiable.

Motivation

Structural
Subsumption
Algorithms

**Tableau
Subsumption
Method**

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Example: Subsumption in a TBox

Example

TBox:

Hermaphrodite \doteq Male \sqcap Female

Parent-of-sons-and-daughters \doteq

\exists has-child.Male \sqcap \exists has-child.Female

Parent-of-hermaphrodite \doteq \exists has-child.Hermaphrodite

Query:

Parent-of-sons-and-daughters $\sqsubseteq_{\mathcal{T}}$

Parent-of-hermaphrodites

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Reductions

1 Unfolding:

$$\begin{aligned} & \exists \text{has-child.Male} \sqcap \exists \text{has-child.Female} \\ & \sqsubseteq \exists \text{has-child.}(\text{Male} \sqcap \text{Female}) \end{aligned}$$

2 Reduction to unsatisfiability: Is the concept

$$\begin{aligned} & \exists \text{has-child.Male} \sqcap \exists \text{has-child.Female} \sqcap \\ & \neg \exists \text{has-child.}(\text{Male} \sqcap \text{Female}) \end{aligned}$$

unsatisfiable?

3 Negation normal form (move negations inside):

$$\begin{aligned} & \exists \text{has-child.Male} \sqcap \exists \text{has-child.Female} \sqcap \\ & \forall \text{has-child.}(\neg \text{Male} \sqcup \neg \text{Female}) \end{aligned}$$

4 Try to construct a model

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Model construction (1)

- 1 **Assumption:** There exists an object x in the interpretation of our concept:

$$x \in (\exists \dots)^{\mathcal{I}}$$

- 2 This implies that x is in the interpretation of all conjuncts:

$$x \in (\exists \text{has-child.Male})^{\mathcal{I}}$$

$$x \in (\exists \text{has-child.Female})^{\mathcal{I}}$$

$$x \in (\forall \text{has-child.}(\neg \text{Male} \sqcup \neg \text{Female}))^{\mathcal{I}}$$

- 3 This implies that there should be objects y and z such that $(x, y) \in \text{has-child}^{\mathcal{I}}$, $(x, z) \in \text{has-child}^{\mathcal{I}}$, $y \in \text{Male}^{\mathcal{I}}$ and $z \in \text{Female}^{\mathcal{I}}$, and ...

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity


ABox Reasoning

Literature

Model construction (2)

$x : \exists \text{has-child.Male}$

$x : \exists \text{has-child.Female}$



-

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning


Literature

Model construction (3)

$x : \exists \text{has-child.Male}$

$x : \exists \text{has-child.Female}$

$x : \forall \text{has-child.}(\neg \text{Male} \sqcup \neg \text{Female})$



-

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature


Model construction (4)

$x : \exists \text{has-child.Male}$

$x : \exists \text{has-child.Female}$

$x : \forall \text{has-child.}(\neg \text{Male} \sqcup \neg \text{Female})$

$y : \neg \text{Male}$



Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Model construction (5)


$x : \exists \text{has-child.Male}$

$x : \exists \text{has-child.Female}$

$x : \forall \text{has-child.}(\neg \text{Male} \sqcup \neg \text{Female})$

$y : \neg \text{Female}$

$z : \neg \text{Male}$



\rightsquigarrow Model constructed!

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Tableau method (1): NNF

We write: $C \equiv D$ iff $C \sqsubseteq D$ and $D \sqsubseteq C$. Now we have the following equivalences:

$$\begin{aligned}\neg(C \sqcap D) &\equiv \neg C \sqcup \neg D & \neg(C \sqcup D) &\equiv \neg C \sqcap \neg D \\ \neg(\forall r.C) &\equiv \exists r.\neg C & \neg(\exists r.C) &\equiv \forall r.\neg C \\ \neg\neg C &\equiv C\end{aligned}$$

These equivalences can be used to move all negations signs to the inside, resulting in concept description where only concept names are negated: **negation normal form (NNF)**.

Theorem (NNF)

The negation normal form of an \mathcal{ALC} concept can be computed in polynomial time.

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Tableau method (2): Constraint systems

A **constraint** is a syntactical object of the form:

$$x : C \quad \text{or} \quad x r y,$$

where C is a concept description in NNF, r is a role name, and x and y are **variable names**.

Let \mathcal{I} be an interpretation with universe \mathcal{D} . An **\mathcal{I} -assignment** α is a function that maps each variable symbol to an object of the universe \mathcal{D} .

A constraint $x : C$ ($x r y$) is **satisfied** by an \mathcal{I} -assignment α if $\alpha(x) \in C^{\mathcal{I}}$ (resp. $(\alpha(x), \alpha(y)) \in r^{\mathcal{I}}$).

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction
Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Tableau method (3): Constraint systems

Definition

A **constraint system** S is a finite, non-empty set of constraints.
An \mathcal{I} -assignment α **satisfies** S if α satisfies each constraint in S .
 S is **satisfiable** if there exist \mathcal{I} and α such that α satisfies S .

Theorem

An \mathcal{ALC} concept C in NNF is satisfiable if and only if the system $\{x : C\}$ is satisfiable.

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction
Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Tableau method (4): Transforming constraint systems

Transformation rules:

- $S \rightarrow_{\sqcap} \{x: C_1, x: C_2\} \cup S$
if $(x: C_1 \sqcap C_2) \in S$ and either $(x: C_1)$ or $(x: C_2)$ or both are not in S .
- $S \rightarrow_{\sqcup} \{x: D\} \cup S$
if $(x: C_1 \sqcup C_2) \in S$ and neither $(x: C_1) \in S$ nor $(x: C_2) \in S$ and $D = C_1$ or $D = C_2$.
- $S \rightarrow_{\exists} \{xry, y: C\} \cup S$
if $(x: \exists r.C) \in S$, y is a **fresh variable**, and there is no z s.t. $(xrz) \in S$ and $(z: C) \in S$.
- $S \rightarrow_{\forall} \{y: C\} \cup S$
if $(x: \forall r.C), (xry) \in S$ and $(y: C) \notin S$.

Notice: Deterministic rules (1,3,4) vs. non-deterministic (2).

Generating rules (3) vs. non-generating (1,2,4).

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

**Transforming
Constraint Systems**

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Tableau method (5): Invariances

Theorem (Invariance)

Let S and T be constraint systems.

- 1 If T has been generated by applying a deterministic rule to S , then S is satisfiable if and only if T is satisfiable.*
- 2 If T has been generated by applying a non-deterministic rule to S , then S is satisfiable if T is satisfiable. Furthermore, if a non-deterministic rule can be applied to S , then it can be applied such that S is satisfiable if and only if the resulting system T is satisfiable.*

Theorem (Termination)

Let C be an \mathcal{ALC} concept description in NNF. Then there exists no infinite chain of transformations starting from the constraint system $\{x : C\}$

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Tableau method (6): Soundness and completeness

A constraint system is called **closed** if no transformation rule can be applied.

A **clash** is a pair of constraints of the form $x : A$ and $x : \neg A$, where A is a concept name.

Theorem (Soundness and Completeness)

A closed constraint system is satisfiable if and only if it does not contain a clash.

Proof idea.

\Rightarrow : obvious. \Leftarrow : Construct a model by using the concept labels. □

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction
Equivalences & NNF
Constraint Systems

Transforming
Constraint Systems
Invariances

**Soundness and
Completeness**

Space Complexity
ABox Reasoning

Literature

Space requirements

Because the tableau method is **non-deterministic** (\rightarrow_{\sqcup} rule), there could be exponentially many closed constraint systems in the end.

Interestingly, applying the rules on a single constraint system can lead to constraint systems of **exponential size**.

Example

$$\begin{aligned} & \exists r. A \sqcap \exists r. B \sqcap \\ & \forall r. (\exists r. A \sqcap \exists r. B \sqcap \\ & \quad \forall r. (\exists r. A \sqcap \exists r. B \sqcap \\ & \quad \quad \forall r. (\dots))) \end{aligned}$$

However: One can modify the algorithm so that it needs only polynomial space.

Idea: Generate a y only for one $\exists r. C$ and then proceed into the depth.

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

ABox reasoning

ABox satisfiability can also be decided using the tableau method if we can add constraints of the form $x \neq y$ (for **UNA**):

- **Normalize** and **unfold** and add inequalities for all pairs of objects mentioned in the ABox.
- Strictly speaking, in *ALC* we do not need this because we are never **forced** to identify two objects.

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Example

Reductions:
Unfolding &
Unsatisfiability

Model Construction

Equivalences & NNF

Constraint Systems

Transforming
Constraint Systems

Invariances

Soundness and
Completeness

Space Complexity

ABox Reasoning

Literature

Literature I

 Baader, F., D. Calvanese, D. L. McGuinness, D. Nardi, and P. F. Patel-Schneider.

The Description Logic Handbook: Theory, Implementation, Applications,

Cambridge University Press, Cambridge, UK, 2003.



Hector J. Levesque and Ronald J. Brachman.

Expressiveness and tractability in knowledge representation and reasoning.

Computational Intelligence, 3:78–93, 1987.



Manfred Schmidt-Schauß and Gert Smolka.

Attributive concept descriptions with complements.

Artificial Intelligence, 48:1–26, 1991.



Bernhard Hollunder and Werner Nutt.

Subsumption Algorithms for Concept Languages.

DFKI Research Report RR-90-04. DFKI, Saarbrücken, 1990. Revised version of paper that was published at ECAI-90.

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Literature

Literature II

Motivation

Structural
Subsumption
Algorithms

Tableau
Subsumption
Method

Literature



F. Baader and U. Sattler.

An Overview of Tableau Algorithms for Description Logics.

Studia Logica, 69:5-40, 2001.



I. Horrocks, U. Sattler, and S. Tobies.

Practical Reasoning for Very Expressive Description Logics.

Logic Journal of the IGPL, 8(3):239-264, May 2000.