

Principles of Knowledge Representation and Reasoning

Nonmonotonic Reasoning

Bernhard Nebel, Felix Lindner, and Thorsten Engesser

14.06. & 19.06.2018

1 Introduction

- Motivation
- Different forms of reasoning
- Different formalizations

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

A reasoning task

- *If Mary has an essay to write, she will study late in the library.*
- *If the library is open, she will study late in the library.*
- *She has an essay to write.*

Conclusion?

- *She will study late in the library.*

Reasoning tasks like this ([suppression task](#); Byrne, 1989) suggest that humans often do not reason as suggested by classical logics

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

Nonmonotonic reasoning

How can we deal with the reasoning task given in the example?

We can use a different representation that allows to restate the task as follows:

- *If Mary has an essay to write, she usually will study late in the library.*
- *She has an essay to write.*
- *If the library is not open, she will not study late in the library.*
- ...

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

Nonmonotonic reasoning

- All logics presented so far are monotonic.
- A logic is called **monotonic** if all (logical) conclusions from a knowledge base remain justified when new information is added to the knowledge base.
- Cognitive studies indicate that everyday reasoning is often nonmonotonic (Stenning & Lambalgen, 2008; Johnson-Laird, 2010, etc.).
- When humans reason they use:
 - rules that may have **exceptions**:
If Mary has an essay to write, she normally will study late in the library.
 - **default** assumptions:
The library is open.

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

Defaults in knowledge bases

Often we use **default** assumptions when definite information is not available or when we want to fix a standard value:

- 1 employee(anne)
- 2 employee(bert)
- 3 employee(carla)
- 4 employee(detlef)
- 5 employee(thomas)
- 6 onUnpaidMPaternityLeave(thomas)
- 7 $\text{employee}(X) \wedge \neg \text{onUnpaidMPaternityLeave}(X) \rightarrow \text{gettingSalary}(X)$
- 8 **Typically:** $\text{employee}(X) \rightarrow \neg \text{onUnpaidMPaternityLeave}(X)$

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

Defaults in common sense reasoning

- 1 **Tweety** is a **bird** like other birds.
- 2 During the summer he stays in **Northern Europe**, in the winter he stays in **Africa**.
 - Would you expect Tweety to be able to fly?
 - How does Tweety get from Northern Europe to Africa?

How would you formalize this in **formal logic** so that you get the expected answers?

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

A formalization ...

- 1 `bird(tweety)`
 - 2 `spend-summer(tweety, northern-europe) ∧
spend-winter(tweety, africa)`
 - 3 $\forall x(\text{bird}(x) \rightarrow \text{can-fly}(x))$
 - 4 `far-away(northern-europe, africa)`
 - 5 $\forall xyz(\text{can-fly}(x) \wedge \text{far-away}(y, z) \wedge \text{spend-summer}(x, y) \wedge \text{spend-winter}(x, z) \rightarrow \text{flies}(x, y, z))$
- **But:** The implication (3) is just a **reasonable assumption**.
 - What if Tweety is an **emu**?

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

Examples of such reasoning patterns

Closed world assumption: Database of **ground atoms**. All ground atoms not present are **assumed** to be false.

Negation as failure: In PROLOG, **NOT(P)** means “*P is not provable*” instead of “*P is provably false*”.

Non-strict inheritance: An attribute value is **inherited** only if there is no more specialized information contradicting the attribute value.

Reasoning about actions: When reasoning about actions, it is usually assumed that a property **changes** only if it **has to change**, i.e., properties by default do not change.

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

Default, defeasible, and nonmonotonic reasoning

Default reasoning: Jump to a conclusion if there is no information that contradicts the conclusion.

Defeasible reasoning: Reasoning based on assumptions that can turn out to be wrong: conclusions are defeasible. In particular, default reasoning is defeasible.

Nonmonotonic reasoning: In classical logic, the set of consequences grows monotonically with the set of premises. If reasoning is defeasible, then reasoning becomes nonmonotonic.

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

Approaches to nonmonotonic reasoning

- **Consistency-based:** Extend classical theory by rules that test whether an assumption is consistent with existing beliefs
- ⇒ Nonmonotonic logics such as DL (default logic), NMLP (nonmonotonic logic programming)
- **Entailment-based on normal models:** Models are ordered by normality. Entailment is determined by considering the most normal models only.
- ⇒ Circumscription, preferential and cumulative logics

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

NM Logic – Consistency-based

If φ typically implies ψ , φ is given, and it is consistent to assume ψ , then conclude ψ .

1 Typically $\text{bird}(x)$ implies $\text{can-fly}(x)$

2 $\forall x(\text{emu}(x) \rightarrow \text{bird}(x))$

3 $\forall x(\text{emu}(x) \rightarrow \neg \text{can-fly}(x))$

4 $\text{bird}(\text{tweety})$

$\Rightarrow \text{can-fly}(\text{tweety})$

5 ... + $\text{emu}(\text{tweety})$

$\Rightarrow \neg \text{can-fly}(\text{tweety})$

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

NM Logic – Normal models

If φ typically implies ψ , then the models satisfying $\varphi \wedge \psi$ should be more normal than those satisfying $\varphi \wedge \neg\psi$.

Similar idea: try to minimize the interpretation of “Abnormality” predicates.

- 1 $\forall x(\text{bird}(x) \wedge \neg\text{Ab}(x) \rightarrow \text{can-fly}(x))$
- 2 $\forall x(\text{emu}(x) \rightarrow \text{bird}(x))$
- 3 $\forall x(\text{emu}(x) \rightarrow \neg\text{can-fly}(x))$
- 4 $\text{bird}(\text{tweety})$

Minimize interpretation of Ab:

$\Rightarrow \text{can-fly}(\text{tweety})$

- 5 ... + $\text{emu}(\text{tweety})$

\Rightarrow Now in all models (incl. the normal ones): $\neg \text{can-fly}(\text{tweety})$

Introduction

Motivation

Different forms of reasoning

Different formalizations

Default Logic

Complexity

Special Kinds of Defaults

Literature

2 Default Logic

- Basics
- Extensions
- Properties of extensions
- Normal defaults
- Default proofs
- Decidability

Introduction

Default Logic

Basics

Extensions

Properties of
extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds
of Defaults

Literature

Default Logic – Outline

1 Introduction

2 Default Logic

- Basics
- Extensions
- Properties of extensions
- Normal defaults
- Default proofs
- Decidability

3 Complexity of Default Logic

4 Special Kinds of Defaults

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

Reiter's default logic: motivation

- We want to express something like “typically birds fly”.
- Add non-logical inference rule

$$\frac{\text{bird}(x) : \text{can-fly}(x)}{\text{can-fly}(x)}$$

with the intended meaning:

If x is a bird and if it is consistent to assume that x can fly, then conclude that x can fly.

- Exceptions can be represented as formulae:

$$\forall x(\text{penguin}(x) \rightarrow \neg \text{can-fly}(x))$$

$$\forall x(\text{emu}(x) \rightarrow \neg \text{can-fly}(x))$$

$$\forall x(\text{kiwi}(x) \rightarrow \neg \text{can-fly}(x))$$

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

- **FOL** with classical provability relation \vdash and deductive closure: $\text{Th}(\Phi) := \{\varphi \mid \Phi \vdash \varphi\}$
- **Default rules:** $\frac{\alpha : \beta}{\gamma}$
 - α : **Prerequisite**: must have been derived before rule can be applied.
 - β : **Consistency condition**: the negation may not be derivable.
 - γ : **Consequence**: will be concluded.
- A default rule is **closed** if it does not contain free variables.
- **(Closed) default theory**: A pair $\langle D, W \rangle$, where D is a countable set of (closed) default rules and W is a countable set of FOL formulae.

Extensions of default theories

Default theories **extend** the theory given by W using the default rules in D (\rightsquigarrow **extensions**). There may be zero, one, or many extensions.

Example

$$W = \{a, \neg b \vee \neg c\}$$
$$D = \left\{ \frac{a: b}{b}, \frac{a: c}{c} \right\}$$

One **extension** contains b , the other contains c .

Intuitively, an **extension** is a set of **beliefs** resulting from W and D .

Introduction

Default Logic

Basics

Extensions

Properties of
extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds
of Defaults

Literature

Decision problems about extensions in default logic

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

Existence of extensions: Does a default theory have an extension?

Credulous reasoning: If φ is in at least one extension, φ is a **credulous default conclusion**.

Skeptical reasoning: If φ is in all extensions, φ is a **skeptical default conclusion**.

Extensions (informally)

Desirable properties of an **extension** E of $\langle D, W \rangle$:

- 1 Contains all facts: $W \subseteq E$.
- 2 Is deductively closed: $E = \text{Th}(E)$.
- 3 All applicable default rules have been applied:

If

- 1 $(\frac{\alpha:\beta}{\gamma}) \in D$,
- 2 $\alpha \in E$,
- 3 $\neg\beta \notin E$

then $\gamma \in E$.

- Further requirement: Application of default rules must follow in sequence (**groundedness**).

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

Example

$$W = \emptyset$$

$$D = \left\{ \frac{a: b}{b}, \frac{b: a}{a} \right\}$$

Question: Should $\text{Th}(\{a, b\})$ be an extension?

Answer: No!

a can only be derived if we already have derived b .

b can only be derived if we already have derived a .

Introduction

Default Logic

Basics

Extensions

Properties of
extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds
of Defaults

Literature

Extensions (formally)

Definition

Let $\Delta = \langle D, W \rangle$ be a closed default theory.

Let E be any set of closed formulae.

Define:

$$E_0 = W$$

$$E_i = \text{Th}(E_{i-1}) \cup \left\{ \gamma \mid \frac{\alpha : \beta}{\gamma} \in D, \alpha \in E_{i-1}, \neg\beta \notin E \right\}$$

E is called an **extension** of Δ if

$$E = \bigcup_{i=0}^{\infty} E_i.$$

Introduction

Default Logic

Basics

Extensions

Properties of
extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds
of Defaults

Literature

How to use this definition?

- The definition does not tell us how to **construct** an extension.
- However, it tells us how to **check** whether a set is an extension:
 - 1 Guess a set E .
 - 2 Then construct sets E_i by starting with W .
 - 3 If $E = \bigcup_{i=0}^{\infty} E_i$, then E is an **extension** of $\langle D, W \rangle$.

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

Examples

$$D = \left\{ \frac{a: b}{b}, \frac{b: a}{a} \right\}$$

$$W = \{a \vee b\}$$

$$D = \left\{ \frac{a: b}{\neg b} \right\}$$

$$W = \emptyset$$

$$D = \left\{ \frac{a: b}{\neg b} \right\}$$

$$W = \{a\}$$

$$D = \left\{ \frac{:a}{a}, \frac{:b}{b}, \frac{:c}{c} \right\}$$

$$W = \{b \rightarrow \neg a \wedge \neg c\}$$

$$D = \left\{ \frac{:c}{\neg d}, \frac{:d}{\neg e}, \frac{:e}{\neg f} \right\}$$

$$W = \emptyset$$

$$D = \left\{ \frac{:c}{\neg d}, \frac{:d}{\neg c} \right\}$$

$$W = \emptyset$$

$$D = \left\{ \frac{a: b}{c}, \frac{a: d}{e} \right\}$$

$$W = \{a, \neg b \vee \neg d\}$$

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

Questions, questions, questions ...

- What can we say about the **existence** of extensions?
- How are the different extensions **related** to each other?
 - Can one extension be a **subset** of another one?
 - Are extensions **pairwise incompatible** (i.e. jointly inconsistent)?
- Can an extension be **inconsistent**?

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

Properties of extensions: existence

Theorem

- 1 *If W is inconsistent, there is only one extension.*
- 2 *A closed default theory $\langle D, W \rangle$ has an inconsistent extensions E if and only if W is inconsistent.*

Proof idea.

- 1 If W is inconsistent, no default rule is applicable and $\text{Th}(W)$ is the only extension (which is inconsistent as well).
- 2 Claim 1 \Rightarrow the **if**-part.
For **only if**: Let W be consistent and assume that there exists an inconsistent extension E .
Then there exists a consistent E_i such that E_{i+1} is inconsistent.
That is, there is at least one applied default $\alpha_i: \beta_i / \gamma_i$ with $\gamma_i \in E_{i+1} \setminus \text{Th}(E_i)$, $\alpha_i \in E_i$, and $\neg\beta_i \notin E$.
But this contradicts the inconsistency of E .

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature



Properties of extensions

Theorem

If E and F are extensions of $\langle D, W \rangle$ such that $E \subseteq F$, then $E = F$.

Proof sketch.

$E = \bigcup_{i=0}^{\infty} E_i$ and $F = \bigcup_{i=0}^{\infty} F_i$. Use induction to show $F_i \subseteq E_i$.

Base case $i = 0$: Trivially $E_0 = F_0 = W$.

Inductive case $i \geq 1$: Assume $\gamma \in F_{i+1}$. Two cases:

- 1 $\gamma \in \text{Th}(F_i)$ implies $\gamma \in \text{Th}(E_i)$ (because $F_i \subseteq E_i$ by IH), and therefore $\gamma \in E_{i+1}$.
- 2 Otherwise $\frac{\alpha:\beta}{\gamma} \in D$, $\alpha \in F_i$, $\neg\beta \notin F$. However, then we have $\alpha \in E_i$ (because $F_i \subseteq E_i$) and $\neg\beta \notin E$ (because of $E \subseteq F$), i.e., $\gamma \in E_{i+1}$. □

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

Normal default theories

All defaults in a **normal default theory** are **normal**:

$$\frac{\alpha : \beta}{\beta}.$$

Theorem

Normal default theories have at least one extension.

Proof sketch.

If W inconsistent, trivial.

Otherwise construct

$$\begin{aligned} E_0 &= W \\ E_{i+1} &= \text{Th}(E_i) \cup T_i \end{aligned} \quad E = \bigcup_{i=0}^{\infty} E_i$$

where T_i is a maximal set s.t. (1) $E_i \cup T_i$ is consistent and (2) if $\beta \in T_i$ then there is $\frac{\alpha : \beta}{\beta} \in D$ and $\alpha \in E_i$.

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

Normal default theories: extensions are orthogonal

Theorem (Orthogonality)

*Let E and F be distinct extensions of a normal default theory.
Then $E \cup F$ is inconsistent.*

Proof.

Let $E = \bigcup E_i$ and $F = \bigcup F_i$ with

$$E_{i+1} = \text{Th}(E_i) \cup \left\{ \beta \mid \frac{\alpha: \beta}{\beta} \in D, \alpha \in E_i, \neg\beta \notin E \right\}$$

and the same for F .

Since $E \neq F$, there exists a smallest i such that $E_{i+1} \neq F_{i+1}$. This means there exists $\frac{\alpha: \beta}{\beta} \in D$ with $\alpha \in E_i = F_i$, but with, say, $\beta \in E_{i+1}$ and $\beta \notin F_{i+1}$. This is only possible if $\neg\beta \in F$.

This means, $\beta \in E$ and $\neg\beta \in F$, i.e., $E \cup F$ is inconsistent. □

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

Default proofs in normal default theories

Definition

A **default proof** of γ in a normal default theory $\langle D, W \rangle$ is a finite sequence of defaults $(\delta_i = \frac{\alpha_i : \beta_i}{\beta_i})_{i=1, \dots, n}$ in D such that

- 1 $W \cup \{\beta_1, \dots, \beta_n\} \vdash \gamma$,
- 2 $W \cup \{\beta_1, \dots, \beta_n\}$ is consistent, and
- 3 $W \cup \{\beta_1, \dots, \beta_k\} \vdash \alpha_{k+1}$, for $0 \leq k \leq n - 1$.

Theorem

Let $\Delta = \langle D, W \rangle$ be a normal default theory so that W is consistent. Then γ has a default proof in Δ if and only if there exists an extension E of Δ such that $\gamma \in E$.

Test 2 (**consistency**) in the proof procedure suggests that default provability is not even **semi-decidable**.

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

Theorem

It is not semi-decidable to test whether a formula follows (skeptically or credulously) from a default theory.

Proof.

Let $\langle D, W \rangle$ be a default theory with $W = \emptyset$ and $D = \left\{ \frac{\cdot}{\beta} \right\}$ with β an arbitrary closed FOL formula. Clearly, β is in some/all extensions of $\langle D, W \rangle$ if and only if β is satisfiable.

The existence of a semi-decision procedure for default proofs implies that there is a semi-decision procedure for satisfiability in FOL.

But this is not possible because FOL validity is semi-decidable and this together with semi-decidability of FOL satisfiability would imply decidability of FOL, which is not the case. □

Introduction

Default Logic

Basics

Extensions

Properties of extensions

Normal defaults

Default proofs

Decidability

Complexity

Special Kinds of Defaults

Literature

3 Complexity of Default Logic

- Propositional DL
- Complexity of DL

Introduction

Default Logic

Complexity

Propositional DL

Complexity of DL

Special Kinds
of Defaults

Literature

Propositional default logic

- **Propositional DL** is decidable.
- How difficult is reasoning in propositional DL?
- The **skeptical default reasoning** problem (does φ follow from Δ skeptically: $\Delta \mid \sim \varphi$?) is called **PDS**, credulous reasoning is called **LPDS**.
- PDS is **coNP-hard**:
consider $D = \emptyset$, $W = \emptyset$
- LPDS is **NP-hard**:
consider $D = \left\{ \frac{:\beta}{\beta} \right\}$, $W = \emptyset$.

Introduction

Default Logic

Complexity

Propositional DL

Complexity of DL

Special Kinds
of Defaults

Literature

Skeptical reasoning in propositional DL

Lemma

$$PDS \in \Pi_2^p.$$

Proof sketch.

We show that the complementary problem **UNPDS** (is there an extension E such that $\varphi \notin E$) is in Σ_2^p .

The **algorithm**:

- 1 **Guess** set $T \subseteq D$ of defaults, those that are applied.
 - 2 **Verify** that defaults in T lead to E , using a **SAT oracle** and the guessed $E := \text{Th} \left(\left\{ \gamma: \frac{\alpha:\beta}{\gamma} \in T \right\} \cup W \right)$.
 - 3 **Verify** that $\left\{ \gamma: \frac{\alpha:\beta}{\gamma} \in T \right\} \cup W \not\models \varphi$ (**SAT oracle**).
- \rightsquigarrow UNPDS $\in \Sigma_2^p$.

Introduction

Default Logic

Complexity

Propositional DL

Complexity of DL

Special Kinds
of Defaults

Literature



Π_2^p -Hardness

Lemma

PDS is Π_2^p -hard.

Proof sketch.

Reduction from 2- $\forall\exists$ -QBF to PDS: For $\forall \vec{a} \exists \vec{b} \varphi(\vec{a}, \vec{b})$ with $\vec{a} = a_1, \dots, a_n$ and $\vec{b} = b_1, \dots, b_m$ construct $\Delta = \langle D, W \rangle$ with

$$D = \left\{ \frac{: a_i}{a_i}, \frac{: \neg a_i}{\neg a_i}, \frac{: \varphi(\vec{a}, \vec{b})}{\varphi(\vec{a}, \vec{b})} \right\}, \quad W = \emptyset$$

No extension contains both a_i and $\neg a_i$. Then:

$\Delta \models \varphi(\vec{a}, \vec{b})$ iff for all E : $\varphi(\vec{a}, \vec{b}) \in E$ (by $\frac{: \varphi(\vec{a}, \vec{b})}{\varphi(\vec{a}, \vec{b})} \in D$)

iff for all consis. $A \subseteq \{a_1, \neg a_1, \dots, a_n, \neg a_n\}$: $A \not\models \neg \varphi(\vec{a}, \vec{b})$

iff $\forall \vec{a} \exists \vec{b} \varphi(\vec{a}, \vec{b})$ is true. \square

Introduction

Default Logic

Complexity

Propositional DL

Complexity of DL

Special Kinds
of Defaults

Literature

Conclusions & remarks

Theorem

PDS is Π_2^p -complete, even for defaults of the form $\frac{: \alpha}{\alpha}$.

Theorem

LPDS is Σ_2^p -complete, even for defaults of the form $\frac{: \alpha}{\alpha}$.

- PDS is “easier” than reasoning in most modal logics.
- General and normal defaults have the same complexity.
- Polynomial special cases cannot be achieved by restricting, for example, to **Horn clauses** (satisfiability testing in polynomial time).
- It is necessary to restrict the underlying **monotonic reasoning problem** and the **number of extensions**.
- Similar results hold for other **nonmonotonic logics**.

Introduction

Default Logic

Complexity

Propositional DL

Complexity of DL

Special Kinds
of Defaults

Literature

4 Special Kinds of Defaults

- Semi-normal defaults
- Open defaults
- Outlook

Introduction

Default Logic

Complexity

**Special Kinds
of Defaults**

Semi-normal
defaults

Open defaults

Outlook

Literature

Semi-normal defaults (1)

Semi-normal defaults are sometimes useful:

$$\frac{\alpha : \beta \wedge \gamma}{\beta}$$

Important when one has **interacting** defaults:

$$\frac{\text{Adult}(x) : \text{Employed}(x)}{\text{Employed}(x)}$$

$$\frac{\text{Student}(x) : \text{Adult}(x)}{\text{Adult}(x)}$$

$$\frac{\text{Student}(x) : \neg\text{Employed}(x)}{\neg\text{Employed}(x)}$$

For **Student(TOM)** we get two extensions: one with **Employed(TOM)** and the other one with $\neg\text{Employed(TOM)}$. Since the third rule is “**more specific**”, we may prefer it.

Introduction

Default Logic

Complexity

Special Kinds
of Defaults

Semi-normal
defaults

Open defaults

Outlook

Literature

Semi-normal defaults (2)

- Since being a student is an exception, we could use a **semi-normal** default to exclude students from employed adults:

$$\frac{\text{Student}(x) : \neg\text{Employed}(x)}{\neg\text{Employed}(x)}$$
$$\frac{\text{Adult}(x) : \text{Employed}(x) \wedge \neg\text{Student}(x)}{\text{Employed}(x)}$$
$$\frac{\text{Student}(x) : \text{Adult}(x)}{\text{Adult}(x)}$$

- Representing conflict-resolution by semi-normal defaults becomes clumsy when the number of default rules becomes high.
- A scheme for assigning **priorities** would be more elegant (there are indeed such schemes).

Introduction

Default Logic

Complexity

Special Kinds
of Defaults

Semi-normal
defaults

Open defaults

Outlook

Literature

Open defaults (1)

- Our examples included **open defaults**, but the theory covers only **closed defaults**.
- If we have $\frac{\alpha(\vec{x}):\beta(\vec{x})}{\gamma(\vec{x})}$, then the variables should stand for all **nameable** objects.
- **Problem**: What about objects that have been introduced implicitly, e.g., via formulae such a $\exists xP(x)$.
- **Solution by Reiter**: Skolemization of all formulae in W and D .
- **Interpretation**: An open default stands for all the closed defaults resulting from substituting **ground terms** for the variables.

Introduction

Default Logic

Complexity

Special Kinds
of Defaults

Semi-normal
defaults

Open defaults

Outlook

Literature

Open defaults (2)

Skolemization can create problems because it preserves satisfiability, but it is not an equivalence transformation.

Example

$$\forall x(\text{Man}(x) \leftrightarrow \neg \text{Woman}(x))$$

$$\forall x(\text{Man}(x) \rightarrow (\exists y(\text{Spouse}(x, y) \wedge \text{Woman}(y)) \vee \text{Bachelor}(x)))$$

$$\text{Man}(\text{TOM})$$

$$\text{Spouse}(\text{TOM}, \text{MARY})$$

$$\text{Woman}(\text{MARY})$$

$$\frac{: \text{Man}(x)}{\text{Man}(x)}$$

Skolemization of $\exists y$: ... enables concluding $\text{Bachelor}(\text{TOM})!$
The reason is that for $g(\text{TOM})$ we get $\text{Man}(g(\text{TOM}))$ by default
(where g is the Skolem function).

Introduction

Default Logic

Complexity

Special Kinds
of Defaults

Semi-normal
defaults

Open defaults

Outlook

Literature

Open defaults (3)

It is even worse: Logically equivalent theories can have different extensions:

$$\begin{aligned}W_1 &= \{\exists x(P(c, x) \vee Q(c, x))\} \\W_2 &= \{\exists xP(c, x) \vee \exists xQ(c, x)\} \\D &= \left\{ \frac{P(x, y) \vee Q(x, y): R}{R} \right\}\end{aligned}$$

W_1 and W_2 are logically equivalent. However, the Skolemization of W_1 , symbolically $s(W_1)$, is not equivalent with $s(W_2)$. The only extension of $\langle D, W_1 \rangle$ is $\text{Th}(s(W_1) \cup R)$. The only extension of $\langle D, W_2 \rangle$ is $\text{Th}(s(W_2))$.

Note: Skolemization is not the right method to deal with open defaults in the general case.

Introduction

Default Logic

Complexity

Special Kinds
of Defaults

Semi-normal
defaults

Open defaults

Outlook

Literature

Although Reiter's definition of DL makes sense, one can come up with a number of variations and extend the investigation ...

- Extensions can be defined differently (e.g., by remembering consistency conditions).
- ... or by removing the groundedness condition.
- Open defaults can be handled differently (more model-theoretically).
- General proof methods for the finite, decidable case
- Applications of default logic:
 - Diagnosis
 - Reasoning about actions

[Introduction](#)

[Default Logic](#)

[Complexity](#)

[Special Kinds
of Defaults](#)

[Semi-normal
defaults](#)

[Open defaults](#)

[Outlook](#)

[Literature](#)

Literature

Introduction

Default Logic

Complexity

Special Kinds
of Defaults

Literature



Raymond Reiter.

A logic for default reasoning.

Artificial Intelligence, 13(1):81–132, April 1980.



Georg Gottlob.

Complexity results for nonmonotonic logics.

Journal for Logic and Computation, 2(3), 1992.



Marco Cadoli and Marco Schaerf.

A survey of complexity results for non-monotonic logics.

The Journal of Logic Programming 17: 127–160, 1993.



Gerhard Brewka.

Nonmonotonic Reasoning: Logical Foundations of Commonsense.

Cambridge University Press, Cambridge, UK, 1991.