Semantic Networks and Description Logics

Description Logics – Reasoning Services and Reductions

Knowledge Representation and Reasoning

Jan, 2005

Description Logics – Reasoning Services and Reductions

Example TBox & ABox

$$
\begin{aligned}
\texttt{Male} &\doteq \neg\texttt{Female} \\
\texttt{Human} &\sqsubseteq \texttt{Living\_entity} \\
\texttt{Woman} &\doteq \texttt{Human} \sqcap \texttt{Female} \\
\texttt{Man} &\doteq \texttt{Human} \sqcap \texttt{Male} \\
\texttt{Mother} &\doteq \texttt{Woman} \sqcap \exists\texttt{has-child.Human} \\
\texttt{Father} &\doteq \texttt{Man} \sqcap \exists\texttt{has-child.Human} \\
\texttt{Parent} &\doteq \texttt{Father} \sqcup \texttt{Mother} \\
\texttt{Grandmother} & \\
&\doteq \texttt{Woman} \sqcap \exists\texttt{has-child.Parent} \\
\texttt{Mother-without-daughter} & \\
&\doteq \texttt{Mother} \sqcap \forall\texttt{has-child.Male} \\
\texttt{Mother-with-many-children} & \\
&\doteq \texttt{Mother} \sqcap (\geq 3\,\texttt{has-child})
\end{aligned}
$$

DIANA:	Woman	
ELIZABETH:	Woman	
CHARLES:	Man	
EDWARD:	Man	
ANDREW:	Man	
DIANA:	Mother-without-daughter	
(ELIZABETH,	CHARLES):	has-child
(ELIZABETH,	EDWARD):	has-child
(ELIZABETH,	ANDREW):	has-child
(DIANA,	WILLIAM):	has-child
(CHARLES,	WILLIAM):	has-child

Motivation: Reasoning Services

- What do we want to know?
- We want to check whether the *knowledge base* is reasonable:
  - Is each defined concept in a TBox satisfiable?
  - Is a given TBox satisfiable?
  - Is a given ABox satisfiable?
- What can we **conclude** from the represented knowledge?
  - Is concept X **subsumed** by concept Y?
  - Is an object a **instance** of a concept X?

$\rightsquigarrow$ These problems can be **reduced** to logical satisfiability or implication – using the logical semantics.

$\longrightarrow$ We take a different route: We will try to simplify these problems and then we specify *direct inference methods*.

Satisfiability of Concept Descriptions in a TBox

- **Motivation**: Given a TBox $\mathcal{T}$ and a concept description C, does C make sense, i.e., is C **satisfiable**?
- **Test**:
  - Does there exists a *model* $\mathcal{I}$ of $\mathcal{T}$ such that $C^{\mathcal{I}} \neq \emptyset$?
  - Is the formula $\exists x\colon C(x)$ together with the formulas resulting from the translation of $\mathcal{T}$ satisfiable?
- **Example**: $\texttt{Mother-without-daughter} \sqcap \forall \texttt{has-child}.\texttt{Female}$ is unsatisfiable.

Satisfiability of Concept Descriptions (without a TBox)

- **Motivation**: Given a concept description C in "isolation", i.e., in an *empty TBox*, does C make sense, i.e., is C **satisfiable**?
- **Test**:
  - Does there exists an *interpretation* $\mathcal{I}$ such that $C^{\mathcal{I}} \neq \emptyset$?
  - Is the formula $\exists x\colon C(x)$ satisfiable?
- **Example**: $\texttt{Woman} \sqcap (\leq 0\ \texttt{has-child}) \sqcap (\geq 1\ \texttt{has-child})$ is unsatisfiable.

Reduction: Getting Rid of the TBox

- We can **reduce** satisfiability in a TBox to simple satisfiability.
- **Idea**:
  - Since TBoxes are *cycle-free*, one can understand a concept definition as a kind of "macro"
  - For a given TBox $\mathcal{T}$ and a given concept description C, all defined concept symbols appearing in C can be *expanded* until C contains only undefined concept symbols
  - An *expanded* concept description is then satisfiable iff C is satisfiable in $\mathcal{T}$
  - *Problem*: What do we do with partial definitions (using $\sqsubseteq$)?

Normalized Terminologies

- A terminology is called **normalized** when it does not contain definitions using $\sqsubseteq$.
- In order to *normalize* a terminology, replace

$$A \sqsubseteq C$$

by

$$A \doteq A^* \sqcap C,$$

where A^* is a **fresh** concept symbol (not appearing elsewhere in $\mathcal{T}$).
- If $\mathcal{T}$ is a terminology, the normalized terminology is denoted by $\widetilde{\mathcal{T}}$.

Normalizing is Reasonable

Theorem (Normalization Invariance)

If $\mathcal{I}$ is a model of the terminology $\mathcal{T}$, then there exists a model $\mathcal{I}'$ of $\widetilde{\mathcal{T}}$ (and vice versa*) such that for all concept symbols A appearing in $\mathcal{T}$ we have:*

$$A^{\mathcal{I}} = A^{\mathcal{I}'}.$$

Proof.

"$\Rightarrow$": Let $\mathcal{I}$ be a model of $\mathcal{T}$. This model should be *extended* to $\mathcal{I}'$ so that the freshly introduced concept symbols also get extensions. Assume $(A \sqsubseteq C) \in \mathcal{T}$, i.e., we have $(A \doteq A^* \sqcap C) \in \widetilde{\mathcal{T}}$. Then set $A^{*\mathcal{I}'} = A^{\mathcal{I}}$. $\mathcal{I}'$ obviously satisfies $\widetilde{\mathcal{T}}$ and has the same interpretation for all symbols in $\mathcal{T}$.
$\Leftarrow$ Given a model $\mathcal{I}'$ of $\widetilde{\mathcal{T}}$, its restriction to symbols of $\mathcal{T}$ is the interpretation we looked for. $\square$

TBox Unfolding

- We say that a *normalized TBox* is **unfolded by one step** when all defined concept symbols on the right sides are replaced by their defining terms.
- **Example**: $\texttt{Mother} \doteq \texttt{Woman} \sqcap \ldots$ is unfolded to $\texttt{Mother} \doteq (\texttt{Human} \sqcap \texttt{Female}) \sqcap \ldots$
- We write $U(\mathcal{T})$ to denote a one-step unfolding and $U^n(\mathcal{T})$ to denote an *n-step unfolding*.
- We say $\mathcal{T}$ is **unfolded** if $U(\mathcal{T}) = \mathcal{T}$.
- We say that $U^n(\mathcal{T})$ is the **unfolding** of $\mathcal{T}$ if $U^n(\mathcal{T}) = U^{n+1}(\mathcal{T})$. If such an unfolding exists, it is denoted by $\widehat{\mathcal{T}}$

Properties of Unfoldings (1): Existence

Theorem (Existence of unfolded terminology)

For each normalized terminology $\mathcal{T}$, there exists its unfolding $\widehat{\mathcal{T}}$.

Proof idea.

The main reason is that terminologies have to be *cycle-free*. The proof can be done by induction of the *definition depth* of concepts. □

Properties of Unfoldings (2): Equivalence

Theorem (Model equivalence for unfolded terminologies)

$\mathcal{I}$ is a model of a normalized terminology $\mathcal{T}$ iff it is a model of $\widehat{\mathcal{T}}$.

Proof Sketch.

"$\Rightarrow$": Let $\mathcal{I}$ be a model of $\mathcal{T}$. Then it is also a model of $U(\mathcal{T})$, since on the right side of the definitions only terms with identical interpretations are substituted. However, then it must also be a model of $\widehat{\mathcal{T}}$.

"$\Leftarrow$": Let $\mathcal{I}$ be a model for $U(\mathcal{T})$. Clearly, this is also a model of $\mathcal{T}$ (with the same argument as above). This means that any model $\widehat{\mathcal{T}}$ is also a model of $\mathcal{T}$. $\square$

Generating Models

- All concept and role names *not appearing on the left hand side* in a terminology $\mathcal{T}$ are called **primitive components**.
- Interpretations restricted to primitive components are called **initial interpretations**.

Theorem (Model extension)

For each initial interpretation $\mathcal{J}$ of a normalized TBox, there exists a unique interpretation $\mathcal{I}$ extending $\mathcal{J}$ and satisfying $\mathcal{T}$.

Proof idea.

Use $\widehat{\mathcal{T}}$ and compute an interpretation for all defined symbols. □

Corollary (Model existence for TBoxes)

Each TBox has at least one model.

Unfolding of Concept Descriptions

- Similar to the unfolding of TBoxes, we can define **unfolding of concept descriptions**.
- We write $\widehat{C}$ for the **unfolded version** of C.

Theorem (Satisfiability of unfolded concepts)

An concept description C is satisfiable in a terminology $\mathcal{T}$ iff $\widehat{C}$ satisfiable in an empty terminology.

Proof.

"$\Rightarrow$": trivial.
"$\Leftarrow$": Use the interpretation for all the symbols in $\widehat{C}$ to generate an initial interpretation of $\mathcal{T}$. Then extend it to a full model $\mathcal{I}$ of $\mathcal{T}$. This satisfies $\mathcal{T}$ as well as $\widehat{C}$. Since $\widehat{C}^{\mathcal{I}} = C^{\mathcal{I}}$, it satisfies also C. $\square$

Subsumption in a TBox

- **Motivation**: Given a terminology $\mathcal{T}$ and two concept descriptions C and D, is C *subsumed by* (or a *sub-concept* of) D in $\mathcal{T}$ ($C \sqsubseteq_{\mathcal{T}} D$)?
- **Test**:
  - Is C interpreted as a subset of D for all models $\mathcal{I}$ of $\mathcal{T}$ ($C^{\mathcal{I}} \subseteq D^{\mathcal{I}}$)?
  - Is the formula $\forall x : \big(C(x) \rightarrow D(x)\big)$ a logical consequence of the translation of $\mathcal{T}$ to predicate logic?
- **Example**: $\texttt{Grandmother} \sqsubseteq_{\mathcal{T}} \texttt{Mother}$

Subsumption (Without a TBox)

- **Motivation**: Given two concept descriptions C and D, is C *subsumed by* D regardless of a TBox (or in an *empty TBox*), written $C \sqsubseteq D$?
- **Test**:
  - Is C interpreted as a subset of D for *all interpretations* $\mathcal{I}$ ($C^{\mathcal{I}} \subseteq D^{\mathcal{I}}$)?
  - Is the formula $\forall x : \big(C(x) \rightarrow D(x)\big)$ *logically valid*?
- **Example**: $\texttt{Human} \sqcap \texttt{Female} \sqsubseteq \texttt{Human}$

Reductions

- Subsumption in a TBox can be reduced to subsumption in the empty TBox

$\leadsto$ *Normalize* and *unfold* TBox and concept descriptions.

- Subsumption in the empty TBox can be reduced to unsatisfiability

$\leadsto$ $C \sqsubseteq D$ iff $C \sqcap \neg D$ is unsatisfiable

- Unsatisfiability can be reduced to subsumption

$\leadsto$ C is unsatisfiable iff $C \sqsubseteq (C \sqcap \neg C)$

Classification

- **Motivation**: Compute all subsumption relationships (and represent them using only a minimal number of relationships) in order to
  - check the modeling – does the terminology make sense?
  - use the precomputed relations later when subsumption queries have to be answered
  - $\rightsquigarrow$ reduce to subsumption
  - $\longrightarrow$ it is a *generalized sorting* problem!

Example



ABox Satisfiability

- **Motivation**: An ABox should *model* the real world, i.e., it should have a **model**.
- **Test**: Check for a model
- **Example**:

$$\begin{aligned} X &: (\forall r.\neg C) \\ Y &: C \\ (X, Y) &: r \end{aligned}$$

is not satisfiable.

ABox Satisfiability in a TBox

- **Motivation**: Is a given ABox $\mathcal{A}$ compatible with the terminology introduced in $\mathcal{T}$?
- **Test**: Is $\mathcal{T} \cup \mathcal{A}$ satisfiable?
- **Example**: If we extend our example with

  ```
  MARGRET: Woman
  (DIANA,MARGRET): has-child,
  ```

  then the ABox becomes unsatisfiable in the given TBox.
- **Reduction**:
  - to satisfiability of an ABox
  - $\rightsquigarrow$ *Normalize* terminology, then *unfold* all concept and role descriptions in the ABox

Instance Relations

- **Motivation**: Which additional ABox formulas of the form $a\colon C$ follow logically from a given ABox and TBox?
- **Test**:
  - Is $a^{\mathcal{I}} \in C^{\mathcal{I}}$ true in all models of $\mathcal{I}$ of $\mathcal{T} \cup \mathcal{A}$?
  - Does the formula $C(a)$ logically follow from the translation of $\mathcal{A}$ and $\mathcal{T}$ to predicate logic?
- **Reductions**:
  - Instance relations wrt. an ABox and a TBox can be reduced to instance relations wrt. ABox.
  - $\rightsquigarrow$ Use *normalization* and *unfolding*
  - Instance relations in an ABox can be reduced to ABox unsatisfiability:

$$a\colon C \text{ holds in } \mathcal{A} \quad \text{iff} \quad \mathcal{A} \cup \{a\colon \neg C\} \text{ is unsatisfiable}$$

Examples

- `ELIZABETH:Mother-with-many-children`?

⇝ yes

- `WILLIAM:` $\neg$ `Female`?

⇝ yes

- `ELIZABETH:Mother-without-daughter`?

⇝ no (no CWA!)

- `ELIZABETH:Grandmother`?

⇝ no (only male, but not necessarily human!)

Realization

- **Idea**: For a given object a, determine the **most specialized concept symbols** such that a is an instance of these concepts
- **Motivation**:
  - Similar to *classification*
  - Is the minimal representation of the instance relations (in the set of concept symbols)
  - Will give us faster answers for instance queries!
- **Reduction**: Can be reduced to (a sequence of) instance relation tests.

Retrieval

- **Motivation**: Sometimes, we want to get the set of instances of a concept (as in database queries)
- **Example**: Asking for all instances of the concept `Male`, we will get the answer `CHARLES`, `ANDREW`, `EDWARD`, `WILLIAM`.
- **Reduction**: Compute the set of instances by testing the instance relation for each object
- **Implementation**: Realization can be used to speed this up

Reasoning Services – Summary

- Satisfiability of concept descriptions
  - in a given TBox or in an empty TBox
- Subsumption between concept descriptions
  - in a given TBox or in an empty TBox
- Classification
- Satisfiability of an ABox
  - in a given TBox or in an empty TBox
- Instance relations in an ABox
  - in a given TBox or in an empty TBox
- Realization
- Retrieval

Outlook

- How to determine *subsumption* between two concept description (in the empty TBox)?
- How to determine *instance relations/ABox satisfiability*?
- How to implement the mentioned reductions *efficiently*?
- Does normalization and unfolding introduce another source of *computational complexity*?