

Principles of Knowledge Representation and Reasoning

Semantic Networks and Description Logics II: Description Logics – Terminology and Notation

Albert-Ludwigs-Universität Freiburg



**UNI
FREIBURG**

Bernhard Nebel, Stefan Wölfl, and Julien Hué

January 16, 2013



Introduction

Introduction

Motivation

History

Systems and
Applications

Description Logics
in a Nutshell

Concepts and Roles

TBox and ABox

Reasoning Services

Outlook

Literature

Appendix

Introduction

Motivation

History

Systems and Applications

Description Logics in a Nutshell

Concepts and Roles

TBox and ABox

Reasoning Services

Outlook

Literature

Appendix

- Main problem with **semantic networks** and **frames**
... the lack of **formal semantics**!
 - Disadvantage of simple **inheritance networks**
... concepts are atomic and do not have any **structure**
- ~> Brachman's **structural inheritance networks** (1977)



- Concepts are **defined/described** using a small set of well-defined operators
- Distinction between **conceptual** and **object-related** knowledge
- Computation of **subconcept relation** and of **instance relation**
- **Strict inheritance** (of the entire structure of a concept): inherited properties cannot be overridden

Introduction

Motivation

History

Systems and
Applications

Description Logics
in a Nutshell

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

■ Systems:

- **KL-ONE**: First implementation of the ideas (1978)
- then: **NIKL**, **KL-TWO**, **KRYPTON**, **KANDOR**, **CLASSIC**, **BACK**, **KRIS**, **YAK**, **CRACK** ...
- later: **FaCT**, **DLP**, **RACER** 1998
- currently: **FaCT++**, **RACER**, **Pellet**.

■ Applications:

- First, natural language understanding systems,
- then configuration systems,
- and information systems,
- currently, it is one tool for the **Semantic Web**

- Languages: **DAML+OIL**, now **OWL** (Web Ontology Language)

Introduction

Motivation

History

Systems and
Applications

Description Logics
in a Nutshell

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

■ Systems:

- **KL-ONE**: First implementation of the ideas (1978)
- then: **NIKL**, **KL-TWO**, **KRYPTON**, **KANDOR**, **CLASSIC**, **BACK**, **KRIS**, **YAK**, **CRACK** ...
- later: **FaCT**, **DLP**, **RACER** 1998
- currently: **FaCT++**, **RACER**, **Pellet**.

■ Applications:

- First, natural language understanding systems,
- then configuration systems,
- and information systems,
- currently, it is one tool for the **Semantic Web**

- Languages: **DAML+OIL**, now **OWL** (Web Ontology Language)

Introduction

Motivation

History

Systems and
Applications

Description Logics
in a Nutshell

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

■ Systems:

- **KL-ONE**: First implementation of the ideas (1978)
- then: **NIKL**, **KL-TWO**, **KRYPTON**, **KANDOR**, **CLASSIC**, **BACK**, **KRIS**, **YAK**, **CRACK** ...
- later: **FaCT**, **DLP**, **RACER** 1998
- currently: **FaCT++**, **RACER**, **Pellet**.

■ Applications:

- First, natural language understanding systems,
- then configuration systems,
- and information systems,
- currently, it is one tool for the **Semantic Web**

- Languages: **DAML+OIL**, now **OWL** (**Web Ontology Language**)

Introduction

Motivation

History

Systems and
Applications

Description Logics
in a Nutshell

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix



- Previously also known as **KL-ONE-like languages**, **frame-based languages**, **terminological logics**, **concept languages**
- **Description Logics (DL)** allow us
 - to describe concepts using **complex descriptions**,
 - to introduce the terminology of an application and to structure it (**TBox**),
 - to introduce objects and relate them to the introduced terminology (**ABox**),
 - and to **reason** about the terminology and the objects.

Introduction

Motivation

History

Systems and
Applications

Description Logics
in a Nutshell

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix



- Previously also known as **KL-ONE-like languages**, **frame-based languages**, **terminological logics**, **concept languages**
- **Description Logics (DL)** allow us
 - to describe concepts using **complex descriptions**,
 - to introduce the terminology of an application and to structure it (**TBox**),
 - to introduce objects and relate them to the introduced terminology (**ABox**),
 - and to **reason** about the terminology and the objects.

Introduction

Motivation

History

Systems and
Applications

Description Logics
in a Nutshell

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

Informal example



Male is:	the opposite of female
A human is a kind of:	living entity
A woman is:	a human and a female
A man is:	a human and a male
A mother is:	a woman with at least one child that is a human
A father is:	a man with at least one child that is a human
A parent is:	a mother or a father
A grandmother is:	a woman, with at least one child that is a parent
A mother-wod is:	a mother with only male children

Elizabeth is a woman
Elizabeth has the child
Charles
Charles is a man
Diana is a mother-wod
Diana has the child William

Possible Questions :

Is a grandmother a parent?
Is Diana a parent?
Is William a man?
Is Elizabeth a mother-wod?

Introduction

Motivation

History

Systems and
Applications

Description Logics
in a Nutshell

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

Informal example



Male is:	the opposite of female
A human is a kind of:	living entity
A woman is:	a human and a female
A man is:	a human and a male
A mother is:	a woman with at least one child that is a human
A father is:	a man with at least one child that is a human
A parent is:	a mother or a father
A grandmother is:	a woman, with at least one child that is a parent
A mother-wod is:	a mother with only male children

Elizabeth is a woman

Elizabeth has the child

Charles

Charles is a man

Diana is a mother-wod

Diana has the child William

Possible Questions :

Is a grandmother a parent?

Is Diana a parent?

Is William a man?

Is Elizabeth a mother-wod?

Introduction

Motivation

History

Systems and
Applications

Description Logics
in a Nutshell

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix



Concepts and Roles

Introduction

**Concepts
and Roles**

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

■ Concept names:

- E.g., Grandmother, Male, ... (in the following usually **capitalized**)
- We will use **symbols** such as A, A_1, \dots for concept names
- **Semantics**: Monadic predicates $A(\cdot)$ or set-theoretically a subset of the universe $A^{\mathcal{I}} \subseteq \mathcal{D}$.

■ Role names:

- In our example, e.g., *child*. Often we will use names such as *has-child* or something similar (in the following usually **lowercase**).
- Role names are **disjoint** from concept names
- **Symbolically**: t, t_1, \dots
- **Semantics**: Binary relations $t(\cdot, \cdot)$ or set-theoretically $t^{\mathcal{I}} \subseteq \mathcal{D} \times \mathcal{D}$.

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

■ Concept names:

- E.g., Grandmother, Male, ... (in the following usually **capitalized**)
- We will use **symbols** such as A, A_1, \dots for concept names
- **Semantics**: Monadic predicates $A(\cdot)$ or set-theoretically a subset of the universe $A^{\mathcal{I}} \subseteq \mathcal{D}$.

■ Role names:

- In our example, e.g., `child`. Often we will use names such as `has-child` or something similar (in the following usually **lowercase**).
- Role names are **disjoint** from concept names
- **Symbolically**: t, t_1, \dots
- **Semantics**: Binary relations $t(\cdot, \cdot)$ or set-theoretically $t^{\mathcal{I}} \subseteq \mathcal{D} \times \mathcal{D}$.

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- From (atomic) **concept** and **role names**, **complex concept and role descriptions** can be created
- In our example, e.g., “Human and Female.”
- **Symbolically**: C for concept descriptions and r for role descriptions

Which particular constructs are available depends on the chosen description logic!

- **FOL semantics**: A concept description C corresponds to a formula $C(x)$ with the free variable x .
Similarly with role descriptions r : they correspond to formulae $r(x,y)$ with free variables x,y .
- **Set semantics**:

$$C^{\mathcal{I}} = \{d \in \mathcal{D} : C(d) \text{ “is true in” } \mathcal{I}\}$$

$$r^{\mathcal{I}} = \{(d,e) \in \mathcal{D}^2 : r(d,e) \text{ “is true in” } \mathcal{I}\}$$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- From (atomic) **concept** and **role names**, **complex concept and role descriptions** can be created
- In our example, e.g., “Human and Female.”
- **Symbolically**: C for concept descriptions and r for role descriptions

Which particular constructs are available depends on the chosen description logic!

- **FOL semantics**: A concept description C corresponds to a formula $C(x)$ with the free variable x .
Similarly with role descriptions r : they correspond to formulae $r(x,y)$ with free variables x,y .
- **Set semantics**:

$$C^{\mathcal{I}} = \{d \in \mathcal{D} : C(d) \text{ “is true in” } \mathcal{I}\}$$

$$r^{\mathcal{I}} = \{(d,e) \in \mathcal{D}^2 : r(d,e) \text{ “is true in” } \mathcal{I}\}$$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- From (atomic) **concept** and **role names**, **complex concept and role descriptions** can be created
- In our example, e.g., “Human and Female.”
- **Symbolically**: C for concept descriptions and r for role descriptions

Which particular constructs are available depends on the chosen description logic!

- **FOL semantics**: A concept description C corresponds to a formula $C(x)$ with the free variable x .
Similarly with role descriptions r : they correspond to formulae $r(x, y)$ with free variables x, y .
- **Set semantics**:

$$C^{\mathcal{I}} = \{d \in \mathcal{D} : C(d) \text{ “is true in” } \mathcal{I}\}$$

$$r^{\mathcal{I}} = \{(d, e) \in \mathcal{D}^2 : r(d, e) \text{ “is true in” } \mathcal{I}\}$$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- **Syntax:** let C and D be concept descriptions, then the following are also concept descriptions:

- $C \sqcap D$ (concept conjunction)
- $C \sqcup D$ (concept disjunction)
- $\neg C$ (concept negation)

- **Examples:**

- Human \sqcap Female
- Father \sqcup Mother
- \neg Female

- **FOL semantics:** $C(x) \wedge D(x)$, $C(x) \vee D(x)$, $\neg C(x)$

- **Set semantics:** $C^{\mathcal{I}} \cap D^{\mathcal{I}}$, $C^{\mathcal{I}} \cup D^{\mathcal{I}}$, $\mathcal{D} \setminus C^{\mathcal{I}}$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- **Syntax:** let C and D be concept descriptions, then the following are also concept descriptions:

- $C \sqcap D$ (concept conjunction)
- $C \sqcup D$ (concept disjunction)
- $\neg C$ (concept negation)

- **Examples:**

- $\text{Human} \sqcap \text{Female}$
- $\text{Father} \sqcup \text{Mother}$
- $\neg \text{Female}$

- FOL semantics: $C(x) \wedge D(x)$, $C(x) \vee D(x)$, $\neg C(x)$

- Set semantics: $C^{\mathcal{I}} \cap D^{\mathcal{I}}$, $C^{\mathcal{I}} \cup D^{\mathcal{I}}$, $\mathcal{D} \setminus C^{\mathcal{I}}$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- **Syntax:** let C and D be concept descriptions, then the following are also concept descriptions:

- $C \sqcap D$ (concept conjunction)
- $C \sqcup D$ (concept disjunction)
- $\neg C$ (concept negation)

- **Examples:**

- $\text{Human} \sqcap \text{Female}$
- $\text{Father} \sqcup \text{Mother}$
- $\neg \text{Female}$

- **FOL semantics:** $C(x) \wedge D(x)$, $C(x) \vee D(x)$, $\neg C(x)$

- **Set semantics:** $C^{\mathcal{I}} \cap D^{\mathcal{I}}$, $C^{\mathcal{I}} \cup D^{\mathcal{I}}$, $\mathcal{D} \setminus C^{\mathcal{I}}$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- **Syntax:** let C and D be concept descriptions, then the following are also concept descriptions:
 - $C \sqcap D$ (concept conjunction)
 - $C \sqcup D$ (concept disjunction)
 - $\neg C$ (concept negation)
- **Examples:**
 - $\text{Human} \sqcap \text{Female}$
 - $\text{Father} \sqcup \text{Mother}$
 - $\neg \text{Female}$
- **FOL semantics:** $C(x) \wedge D(x)$, $C(x) \vee D(x)$, $\neg C(x)$
- **Set semantics:** $C^{\mathcal{I}} \cap D^{\mathcal{I}}$, $C^{\mathcal{I}} \cup D^{\mathcal{I}}$, $\mathcal{D} \setminus C^{\mathcal{I}}$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

■ Motivation:

- Often we want to describe something by **restricting** the possible “fillers” of a role, e.g. Mother-wod.
- Sometimes we want to say that there is at least a filler of a particular type, e.g. Grandmother

■ Idea: Use **quantifiers** that range over the role-fillers

- $\text{Mother} \sqcap \forall \text{has-child.Man}$
- $\text{Woman} \sqcap \exists \text{has-child.Parent}$

■ FOL semantics:

$$(\exists r.C)(x) = \exists y(r(x,y) \wedge C(y))$$

$$(\forall r.C)(x) = \forall y(r(x,y) \rightarrow C(y))$$

■ Set semantics:

$$(\exists r.C)^{\mathcal{I}} = \{d \in \mathcal{D} : \text{there ex. some } e \text{ s.t. } (d,e) \in r^{\mathcal{I}} \wedge e \in C^{\mathcal{I}}\}$$

$$(\forall r.C)^{\mathcal{I}} = \{d \in \mathcal{D} : \text{for each } e \text{ with } (d,e) \in r^{\mathcal{I}}, e \in C^{\mathcal{I}}\}$$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

■ Motivation:

- Often we want to describe something by **restricting** the possible “fillers” of a role, e.g. Mother-wod.
- Sometimes we want to say that there is at least a filler of a particular type, e.g. Grandmother

■ Idea: Use **quantifiers** that range over the role-fillers

- $\text{Mother} \sqcap \forall \text{has-child.Man}$
- $\text{Woman} \sqcap \exists \text{has-child.Parent}$

■ FOL semantics:

$$(\exists r.C)(x) = \exists y(r(x,y) \wedge C(y))$$

$$(\forall r.C)(x) = \forall y(r(x,y) \rightarrow C(y))$$

■ Set semantics:

$$(\exists r.C)^{\mathcal{I}} = \{d \in \mathcal{D} : \text{there ex. some } e \text{ s.t. } (d,e) \in r^{\mathcal{I}} \wedge e \in C^{\mathcal{I}}\}$$

$$(\forall r.C)^{\mathcal{I}} = \{d \in \mathcal{D} : \text{for each } e \text{ with } (d,e) \in r^{\mathcal{I}}, e \in C^{\mathcal{I}}\}$$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

■ Motivation:

- Often we want to describe something by **restricting** the possible “fillers” of a role, e.g. Mother-wod.
- Sometimes we want to say that there is at least a filler of a particular type, e.g. Grandmother

■ Idea: Use **quantifiers** that range over the role-fillers

- $\text{Mother} \sqcap \forall \text{has-child.Man}$
- $\text{Woman} \sqcap \exists \text{has-child.Parent}$

■ FOL semantics:

$$(\exists r.C)(x) = \exists y(r(x,y) \wedge C(y))$$

$$(\forall r.C)(x) = \forall y(r(x,y) \rightarrow C(y))$$

■ Set semantics:

$$(\exists r.C)^{\mathcal{I}} = \{d \in \mathcal{D} : \text{there ex. some } e \text{ s.t. } (d,e) \in r^{\mathcal{I}} \wedge e \in C^{\mathcal{I}}\}$$

$$(\forall r.C)^{\mathcal{I}} = \{d \in \mathcal{D} : \text{for each } e \text{ with } (d,e) \in r^{\mathcal{I}}, e \in C^{\mathcal{I}}\}$$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

■ Motivation:

- Often we want to describe something by **restricting the number** of possible “fillers” of a role, e.g., a Mother with at least 3 children or at most 2 children.

■ Idea: We restrict the cardinality of the role filler sets:

- $\text{Mother} \sqcap \geq 3 \text{ has-child}$
- $\text{Mother} \sqcap \leq 2 \text{ has-child}$

■ FOL semantics:

$$(\geq n r)(x) = \exists y_1 \dots y_n (r(x, y_1) \wedge \dots \wedge r(x, y_n) \wedge y_1 \neq y_2 \wedge \dots \wedge y_{n-1} \neq y_n)$$

$$(\leq n r)(x) = \neg(\geq n+1 r)(x)$$

■ Set semantics:

$$(\geq n r)^{\mathcal{I}} = \{d \in \mathcal{D} : |\{e \in \mathcal{D} : r^{\mathcal{I}}(d, e)\}| \geq n\}$$

$$(\leq n r)^{\mathcal{I}} = \mathcal{D} \setminus (\geq n+1 r)^{\mathcal{I}}$$

■ Motivation:

- Often we want to describe something by **restricting the number** of possible “fillers” of a role, e.g., a Mother with at least 3 children or at most 2 children.

■ Idea: We restrict the cardinality of the role filler sets:

- $\text{Mother} \sqcap \geq 3 \text{ has-child}$
- $\text{Mother} \sqcap \leq 2 \text{ has-child}$

■ FOL semantics:

$$(\geq n r)(x) = \exists y_1 \dots y_n (r(x, y_1) \wedge \dots \wedge r(x, y_n) \wedge y_1 \neq y_2 \wedge \dots \wedge y_{n-1} \neq y_n)$$

$$(\leq n r)(x) = \neg(\geq n+1 r)(x)$$

■ Set semantics:

$$(\geq n r)^{\mathcal{I}} = \{d \in \mathcal{D} : |\{e \in \mathcal{D} : r^{\mathcal{I}}(d, e)\}| \geq n\}$$

$$(\leq n r)^{\mathcal{I}} = \mathcal{D} \setminus (\geq n+1 r)^{\mathcal{I}}$$

- **Motivation:**
 - How can we describe the concept “children of rich parents”?
- **Idea:** Define the “inverse” role for a given role (the **converse relation**)

■ has-child^{-1}

- **Example:** $\exists \text{has-child}^{-1}.\text{Rich}$

- FOL semantics:

$$r^{-1}(x, y) = r(y, x)$$

- Set semantics:

$$(r^{-1})^{\mathcal{I}} = \{(d, e) \in \mathcal{D}^2 : (e, d) \in r^{\mathcal{I}}\}$$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- Motivation:
 - How can we describe the concept “children of rich parents”?
- Idea: Define the “inverse” role for a given role (the **converse relation**)
 - has-child^{-1}
- Example: $\exists \text{has-child}^{-1}.\text{Rich}$
- FOL semantics:

$$r^{-1}(x, y) = r(y, x)$$

- Set semantics:

$$(r^{-1})^{\mathcal{I}} = \{(d, e) \in \mathcal{D}^2 : (e, d) \in r^{\mathcal{I}}\}$$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- **Motivation:**
 - How can we define the role `has-grandchild` given the role `has-child`?
- **Idea:** Compose roles (as one can compose binary relations)
 - `has-child` \circ `has-child`
- **FOL semantics:**

$$(r \circ s)(x, y) = \exists z (r(x, z) \wedge s(z, y))$$

- **Set semantics:**

$$(r \circ s)^{\mathcal{I}} = \{(d, e) \in \mathcal{D}^2 : \exists f \text{ s.t. } (d, f) \in r^{\mathcal{I}} \wedge (f, e) \in s^{\mathcal{I}}\}$$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

■ Motivation:

- How can we define the role `has-grandchild` given the role `has-child`?

■ Idea: Compose roles (as one can compose binary relations)

- `has-child` \circ `has-child`

■ FOL semantics:

$$(r \circ s)(x, y) = \exists z (r(x, z) \wedge s(z, y))$$

■ Set semantics:

$$(r \circ s)^{\mathcal{I}} = \{(d, e) \in \mathcal{D}^2 : \exists f \text{ s.t. } (d, f) \in r^{\mathcal{I}} \wedge (f, e) \in s^{\mathcal{I}}\}$$

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

■ Motivation:

- How do we express the concept “women who know all the friends of their children”

■ Idea: Relate role filler sets to each other

- $\text{Woman} \sqcap (\text{has-child} \circ \text{has-friend} \sqsubseteq \text{knows})$

■ FOL semantics:

$$(r \sqsubseteq s)(x) = \forall y (r(x, y) \rightarrow s(x, y))$$

■ Set semantics: Let $r^{\mathcal{I}}(d) = \{e : r^{\mathcal{I}}(d, e)\}$.

$$(r \sqsubseteq s)^{\mathcal{I}} = \{d \in \mathcal{D} : r^{\mathcal{I}}(d) \subseteq s^{\mathcal{I}}(d)\}$$

- **Note:** Role value maps lead to undecidability of satisfiability testing of concept descriptions!

Introduction

Concepts
and Roles

Concept Forming
Operators

Role Forming
Operators

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix



TBox and ABox

Introduction

Concepts
and Roles

**TBox and
ABox**

Terminology Box
Assertional Box
Example

Reasoning
Services

Outlook

Literature

Appendix

- In order to **introduce** new terms, we use two kinds of **terminological axioms**:

- $A \doteq C$
- $A \sqsubseteq C$

where A is a **concept name** and C is a **concept description**.

- A **terminology** or **TBox** is a finite set of such axioms with the following additional restrictions:
 - no multiple definitions of the same symbol such as $A \doteq C$,
 $A \sqsubseteq D$
 - no cyclic definitions (even not indirectly), such as $A \doteq \forall r . B$,
 $B \doteq \exists s . A$

Introduction

Concepts
and Roles

TBox and
ABox

Terminology Box
Assertional Box

Example

Reasoning
Services

Outlook

Literature

Appendix

- In order to **introduce** new terms, we use two kinds of **terminological axioms**:

- $A \doteq C$
- $A \sqsubseteq C$

where A is a **concept name** and C is a **concept description**.

- A **terminology** or **TBox** is a finite set of such axioms with the following additional restrictions:
 - no multiple definitions of the same symbol such as $A \doteq C$,
 $A \sqsubseteq D$
 - no cyclic definitions (even not indirectly), such as $A \doteq \forall r . B$,
 $B \doteq \exists s . A$

Introduction

Concepts
and Roles

TBox and
ABox

Terminology Box
Assertional Box

Example

Reasoning
Services

Outlook

Literature

Appendix

- TBoxes restrict the set of possible interpretations.

- **FOL semantics:**

- $A \dot{=} C$ corresponds to $\forall x (A(x) \leftrightarrow C(x))$
- $A \sqsubseteq C$ corresponds to $\forall x (A(x) \rightarrow C(x))$

- **Set semantics:**

- $A \dot{=} C$ corresponds to $A^{\mathcal{I}} = C^{\mathcal{I}}$
- $A \sqsubseteq C$ corresponds to $A^{\mathcal{I}} \subseteq C^{\mathcal{I}}$

- Non-empty interpretations which satisfy all terminological axioms are called **models** of the TBox.

- TBoxes restrict the set of possible interpretations.

- **FOL semantics:**

- $A \dot{=} C$ corresponds to $\forall x (A(x) \leftrightarrow C(x))$
- $A \sqsubseteq C$ corresponds to $\forall x (A(x) \rightarrow C(x))$

- **Set semantics:**

- $A \dot{=} C$ corresponds to $A^{\mathcal{I}} = C^{\mathcal{I}}$
- $A \sqsubseteq C$ corresponds to $A^{\mathcal{I}} \subseteq C^{\mathcal{I}}$

- Non-empty interpretations which satisfy all terminological axioms are called **models** of the TBox.

- TBoxes restrict the set of possible interpretations.
- **FOL semantics:**
 - $A \dot{=} C$ corresponds to $\forall x (A(x) \leftrightarrow C(x))$
 - $A \sqsubseteq C$ corresponds to $\forall x (A(x) \rightarrow C(x))$
- **Set semantics:**
 - $A \dot{=} C$ corresponds to $A^{\mathcal{I}} = C^{\mathcal{I}}$
 - $A \sqsubseteq C$ corresponds to $A^{\mathcal{I}} \subseteq C^{\mathcal{I}}$
- Non-empty interpretations which satisfy all terminological axioms are called **models** of the TBox.

Introduction

Concepts
and Roles

TBox and
ABox

Terminology Box

Assertional Box

Example

Reasoning
Services

Outlook

Literature

Appendix

- In order to state something about objects in the world, we use two forms of **assertions**:

- $a : C$
- $(a, b) : r$

where a and b are **individual names** (e.g., ELIZABETH, PHILIP), C is a **concept description**, and r is a **role description**.

- An **ABox** is a finite set of assertions.

Introduction

Concepts
and Roles

TBox and
ABox

Terminology Box

Assertional Box

Example

Reasoning
Services

Outlook

Literature

Appendix

- **Individual names** are interpreted as elements of the universe under the **unique-name-assumption**, i.e., different names refer to different objects.
- **Assertions** express that an object is an instance of a concept or that two objects are related by a role.
- **FOL semantics:**
 - $a : C$ corresponds to $C(a)$
 - $(a, b) : r$ corresponds to $r(a, b)$
- **Set semantics:**
 - $a^{\mathcal{I}} \in D$
 - $a : C$ corresponds to $a^{\mathcal{I}} \in C^{\mathcal{I}}$
 - $(a, b) : r$ corresponds to $(a^{\mathcal{I}}, b^{\mathcal{I}}) \in r^{\mathcal{I}}$
- **Models** of an ABox and of ABox + TBox can be defined analogously to models of a TBox.

Introduction

Concepts
and Roles

TBox and
ABox

Terminology Box

Assertional Box

Example

Reasoning
Services

Outlook

Literature

Appendix

- **Individual names** are interpreted as elements of the universe under the **unique-name-assumption**, i.e., different names refer to different objects.
- **Assertions** express that an object is an instance of a concept or that two objects are related by a role.
- **FOL semantics:**
 - $a : C$ corresponds to $C(a)$
 - $(a, b) : r$ corresponds to $r(a, b)$
- **Set semantics:**
 - $a^{\mathcal{I}} \in D$
 - $a : C$ corresponds to $a^{\mathcal{I}} \in C^{\mathcal{I}}$
 - $(a, b) : r$ corresponds to $(a^{\mathcal{I}}, b^{\mathcal{I}}) \in r^{\mathcal{I}}$
- **Models** of an ABox and of $\text{ABox} + \text{TBox}$ can be defined analogously to models of a TBox.

Introduction

Concepts
and Roles

TBox and
ABox

Terminology Box

Assertional Box

Example

Reasoning
Services

Outlook

Literature

Appendix

- **Individual names** are interpreted as elements of the universe under the **unique-name-assumption**, i.e., different names refer to different objects.
- **Assertions** express that an object is an instance of a concept or that two objects are related by a role.
- **FOL semantics:**
 - $a : C$ corresponds to $C(a)$
 - $(a, b) : r$ corresponds to $r(a, b)$
- **Set semantics:**
 - $a^{\mathcal{I}} \in D$
 - $a : C$ corresponds to $a^{\mathcal{I}} \in C^{\mathcal{I}}$
 - $(a, b) : r$ corresponds to $(a^{\mathcal{I}}, b^{\mathcal{I}}) \in r^{\mathcal{I}}$
- **Models** of an ABox and of $\text{ABox} + \text{TBox}$ can be defined analogously to models of a TBox.

Introduction

Concepts
and Roles

TBox and
ABox

Terminology Box

Assertional Box

Example

Reasoning
Services

Outlook

Literature

Appendix

Male $\doteq \neg \text{Female}$
Human $\sqsubseteq \text{Living_entity}$
Woman $\doteq \text{Human} \sqcap \text{Female}$
Man $\doteq \text{Human} \sqcap \text{Male}$
Mother $\doteq \text{Woman} \sqcap \exists \text{has-child.Human}$
Father $\doteq \text{Man} \sqcap \exists \text{has-child.Human}$
Parent $\doteq \text{Father} \sqcup \text{Mother}$
Grandmother $\doteq \text{Woman} \sqcap \exists \text{has-child.Parent}$
Mother-without-daughter $\doteq \text{Mother} \sqcap \forall \text{has-child.Male}$
Mother-with-many-children $\doteq \text{Mother} \sqcap (\geq 3 \text{has-child})$

CHARLES: Man
EDWARD: Man
ANDREW: Man
DIANA: Mother-without-daughter
(ELIZABETH, CHARLES): has-child
(ELIZABETH, EDWARD): has-child
(ELIZABETH, ANDREW): has-child
(DIANA, WILLIAM): has-child
(CHARLES, WILLIAM): has-child

DIANA: Woman
ELIZABETH: Woman

[Introduction](#)

[Concepts
and Roles](#)

[TBox and
ABox](#)

[Terminology Box](#)

[Assertional Box](#)

[Example](#)

[Reasoning
Services](#)

[Outlook](#)

[Literature](#)

[Appendix](#)



Reasoning Services

Introduction

Concepts
and Roles

TBox and
ABox

**Reasoning
Services**

Outlook

Literature

Appendix

- Does a description C make sense at all, i.e., is it **satisfiable**?
A concept description C is **satisfiable**, if there exists an interpretation \mathcal{I} such that $C^{\mathcal{I}} \neq \emptyset$.
- Is one concept a specialization of another one, is it **subsumed**?
 C is **subsumed by** D (in symbols $C \sqsubseteq D$) if we have for all interpretations $C^{\mathcal{I}} \subseteq D^{\mathcal{I}}$.
- Is a an **instance** of a concept C ?
 a is an **instance** of C if for all interpretations, we have $a^{\mathcal{I}} \in C^{\mathcal{I}}$.
- **Note:** These questions can be posed with or without a TBox that restricts the possible interpretations.

Introduction

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- Does a description C make sense at all, i.e., is it **satisfiable**?
A concept description C is **satisfiable**, if there exists an interpretation \mathcal{I} such that $C^{\mathcal{I}} \neq \emptyset$.
- Is one concept a specialization of another one, is it **subsumed**?
 C is **subsumed by** D (in symbols $C \sqsubseteq D$) if we have for all interpretations $C^{\mathcal{I}} \subseteq D^{\mathcal{I}}$.
- Is a an **instance** of a concept C ?
 a is an **instance** of C if for all interpretations, we have $a^{\mathcal{I}} \in C^{\mathcal{I}}$.
- **Note:** These questions can be posed with or without a TBox that restricts the possible interpretations.

Introduction

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- Does a description C make sense at all, i.e., is it **satisfiable**?
A concept description C is **satisfiable**, if there exists an interpretation \mathcal{I} such that $C^{\mathcal{I}} \neq \emptyset$.
- Is one concept a specialization of another one, is it **subsumed**?
 C is **subsumed by** D (in symbols $C \sqsubseteq D$) if we have for all interpretations $C^{\mathcal{I}} \subseteq D^{\mathcal{I}}$.
- Is a an **instance** of a concept C ?
 a is an **instance** of C if for all interpretations, we have $a^{\mathcal{I}} \in C^{\mathcal{I}}$.
- *Note:* These questions can be posed with or without a TBox that restricts the possible interpretations.

Introduction

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- Does a description C make sense at all, i.e., is it **satisfiable**?
A concept description C is **satisfiable**, if there exists an interpretation \mathcal{I} such that $C^{\mathcal{I}} \neq \emptyset$.
- Is one concept a specialization of another one, is it **subsumed**?
 C is **subsumed by** D (in symbols $C \sqsubseteq D$) if we have for all interpretations $C^{\mathcal{I}} \subseteq D^{\mathcal{I}}$.
- Is a an **instance** of a concept C ?
 a is an **instance** of C if for all interpretations, we have $a^{\mathcal{I}} \in C^{\mathcal{I}}$.
- **Note:** These questions can be posed with or without a TBox that restricts the possible interpretations.

Introduction

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix



Outlook

Introduction

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

- Can we **reduce** the reasoning services to perhaps just one problem?
- What could be **reasoning algorithms**?
- What can we say about **complexity** and **decidability**?
- What has all that to do with **modal logics**?
- How can one build **efficient systems**?

Introduction

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix



Baader, F., D. Calvanese, D. L. McGuinness, D. Nardi, and P. F. Patel-Schneider.

The Description Logic Handbook: Theory, Implementation, Applications,

Cambridge University Press, Cambridge, UK, 2003.



Ronald J. Brachman and James G. Schmolze.

An overview of the KL-ONE knowledge representation system.

Cognitive Science, 9(2):171–216, April 1985.



Franz Baader, Hans-Jürgen Bürckert, Jochen Heinsohn, Bernhard Hollunder, Jürgen Müller, Bernhard Nebel, Werner Nutt, and Hans-Jürgen Profitlich.

Terminological Knowledge Representation: A proposal for a terminological logic.

Published in Proc. **International Workshop on Terminological Logics**, 1991, DFKI Document D-91-13.

Introduction

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix



Bernhard Nebel.

Reasoning and Revision in Hybrid Representation Systems.

Lecture Notes in Artificial Intelligence 422. Springer-Verlag, Berlin, Heidelberg, New York, 1990.

Introduction

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

Summary: Concept descriptions



Abstract	Concrete	Interpretation
A	A	$A^{\mathcal{I}}$
$C \sqcap D$	(and $C D$)	$C^{\mathcal{I}} \cap D^{\mathcal{I}}$
$C \sqcup D$	(or $C D$)	$C^{\mathcal{I}} \cup D^{\mathcal{I}}$
$\neg C$	(not C)	$\mathcal{D} - C^{\mathcal{I}}$
$\forall r.C$	(all $r C$)	$\{d \in \mathcal{D} : r^{\mathcal{I}}(d) \subseteq C^{\mathcal{I}}\}$
$\exists r$	(some r)	$\{d \in \mathcal{D} : r^{\mathcal{I}}(d) \neq \emptyset\}$
$\geq n r$	(atleast $n r$)	$\{d \in \mathcal{D} : r^{\mathcal{I}}(d) \geq n\}$
$\leq n r$	(atmost $n r$)	$\{d \in \mathcal{D} : r^{\mathcal{I}}(d) \leq n\}$
$\exists r.C$	(some $r C$)	$\{d \in \mathcal{D} : r^{\mathcal{I}}(d) \cap C^{\mathcal{I}} \neq \emptyset\}$
$\geq n r.C$	(atleast $n r C$)	$\{d \in \mathcal{D} : r^{\mathcal{I}}(d) \cap C^{\mathcal{I}} \geq n\}$
$\leq n r.C$	(atmost $n r C$)	$\{d \in \mathcal{D} : r^{\mathcal{I}}(d) \cap C^{\mathcal{I}} \leq n\}$
$r \doteq s$	(eq $r s$)	$\{d \in \mathcal{D} : r^{\mathcal{I}}(d) = s^{\mathcal{I}}(d)\}$
$r \neq s$	(neq $r s$)	$\{d \in \mathcal{D} : r^{\mathcal{I}}(d) \neq s^{\mathcal{I}}(d)\}$
$r \sqsubseteq s$	(subset $r s$)	$\{d \in \mathcal{D} : r^{\mathcal{I}}(d) \subseteq s^{\mathcal{I}}(d)\}$
$g \doteq h$	(eq $g h$)	$\{d \in \mathcal{D} : g^{\mathcal{I}}(d) = h^{\mathcal{I}}(d) \neq \emptyset\}$
$g \neq h$	(neq $g h$)	$\{d \in \mathcal{D} : \emptyset \neq g^{\mathcal{I}}(d) \neq h^{\mathcal{I}}(d) \neq \emptyset\}$
$\{i_1, i_2, \dots, i_n\}$	(one of $i_1 \dots i_n$)	$\{i_1^{\mathcal{I}}, i_2^{\mathcal{I}}, \dots, i_n^{\mathcal{I}}\}$

Introduction

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

Summary: Role Descriptions



Introduction

Concepts
and Roles

TBox and
ABox

Reasoning
Services

Outlook

Literature

Appendix

Abstract	Concrete	Interpretation
t	t	$t^{\mathcal{I}}$
f	f	$f^{\mathcal{I}}$, (functional role)
$r \sqcap s$	(and r s)	$r^{\mathcal{I}} \cap s^{\mathcal{I}}$
$r \sqcup s$	(or r s)	$r^{\mathcal{I}} \cup s^{\mathcal{I}}$
$\neg r$	(not r)	$\mathcal{D} \times \mathcal{D} - r^{\mathcal{I}}$
r^{-1}	(inverse r)	$\{(d, d') : (d', d) \in r^{\mathcal{I}}\}$
$r _C$	(restr r C)	$\{(d, d') \in r^{\mathcal{I}} : d' \in C^{\mathcal{I}}\}$
r^+	(trans r)	$(r^{\mathcal{I}})^+$
$r \circ s$	(compose r s)	$r^{\mathcal{I}} \circ s^{\mathcal{I}}$
$\mathbf{1}$	self	$\{(d, d) : d \in \mathcal{D}\}$