Principles of AI Planning

3. PDDL

Malte Helmert and Bernhard Nebel

Albert-Ludwigs-Universität Freiburg

April 29th, 2010

Schematic operators

Schematic operators

- Description of state variables and operators in terms of a given finite set of objects.
- Analogy: propositional logic vs. predicate logic
- Planners take input as schematic operators and translate them into (ground) operators. This is called grounding.

Schematic operators: example

Schematic operator

$$x \in \{\text{car1}, \text{car2}\}$$
$$y_1 \in \{\text{Freiburg}, \text{Strasbourg}\},$$
$$y_2 \in \{\text{Freiburg}, \text{Strasbourg}\}, y_1 \neq y_2$$

$$\langle \mathit{in}(x, y_1), \mathit{in}(x, y_2) \land \neg \mathit{in}(x, y_1) \rangle$$

corresponds to the operators

$$\langle \mathit{in}(\text{car1}, \text{Freiburg}), \mathit{in}(\text{car1}, \text{Strasbourg}) \land \neg \mathit{in}(\text{car1}, \text{Freiburg}) \rangle,$$
$$\langle \mathit{in}(\text{car1}, \text{Strasbourg}), \mathit{in}(\text{car1}, \text{Freiburg}) \land \neg \mathit{in}(\text{car1}, \text{Strasbourg}) \rangle,$$
$$\langle \mathit{in}(\text{car2}, \text{Freiburg}), \mathit{in}(\text{car2}, \text{Strasbourg}) \land \neg \mathit{in}(\text{car2}, \text{Freiburg}) \rangle,$$
$$\langle \mathit{in}(\text{car2}, \text{Strasbourg}), \mathit{in}(\text{car2}, \text{Freiburg}) \land \neg \mathit{in}(\text{car2}, \text{Strasbourg}) \rangle$$

Schematic operators: quantification

Existential quantification (for formulae only)

Finite disjunctions $\varphi(a_1) \vee \cdots \vee \varphi(a_n)$ represented as $\exists x \in \{a_1, \ldots, a_n\} : \varphi(x)$.

Universal quantification (for formulae and effects)

Finite conjunctions $\varphi(a_1) \wedge \cdots \wedge \varphi(a_n)$ represented as $\forall x \in \{a_1, \ldots, a_n\} : \varphi(x)$.

Example

$\exists x \in \{\mathsf{A}, \mathsf{B}, \mathsf{C}\} : \mathit{in}(x, \mathsf{Freiburg})$ is a short-hand for $\mathit{in}(\mathsf{A}, \mathsf{Freiburg}) \vee \mathit{in}(\mathsf{B}, \mathsf{Freiburg}) \vee \mathit{in}(\mathsf{C}, \mathsf{Freiburg})$.

PDDL

PDDL: the Planning Domain Definition Language

- used by almost all implemented systems for deterministic planning
- supports a language comparable to what we have defined above (including schematic operators and quantification)
- syntax inspired by the Lisp programming language: e.g. prefix notation for formulae

```
(and (or (on A B) (on A C))
     (or (on B A) (on B C))
     (or (on C A) (on A B)))
```

PDDL: domain files

A domain file consists of

- (define (domain DOMAINNAME)
- a :requirements definition (use :adl :typing by default)
- definitions of types (each parameter has a type)
- definitions of predicates
- definitions of operators

Example: blocks world in PDDL

```
(define (domain BLOCKS)
  (:requirements :adl :typing)
  (:types block - object
          blueblock smallblock - block)
  (:predicates (on ?x - smallblock ?y - block)
               (ontable ?x - block)
               (clear ?x - block)
               )
```

PDDL: operator definition

- (:action OPERATORNAME
- list of parameters: (?x - type1 ?y - type2 ?z - type3)
- precondition: a formula

```
<schematic-state-var>
(and <formula> ... <formula>)
(or <formula> ... <formula>)
(not <formula>)
(forall (?x1 - type1 ... ?xn - typen) <formula>)
(exists (?x1 - type1 ... ?xn - typen) <formula>)
```

- effect:

```
<schematic-state-var>
(not <schematic-state-var>)
(and <effect> ... <effect>)
(when <formula> <effect>)
(forall (?x1 - type1 ... ?xn - typen) <effect>)
```

```
(:action fromtable
    :parameters (?x - smallblock ?y - block)
    :precondition (and (not (= ?x ?y))
                       (clear ?x)
                       (ontable ?x)
                       (clear ?y))
    :effect
      (and (not (ontable ?x))
           (not (clear ?y))
           (on ?x ?y)))
```

PDDL: problem files

A problem file consists of

- (define (problem PROBLEMNAME)
- declaration of which domain is needed for this problem
- definitions of objects belonging to each type
- definition of the initial state (list of state variables initially true)
- definition of goal states (a formula like operator precondition)

```
(define (problem example)
  (:domain BLOCKS)
  (:objects a b c - smallblock)
            d e - block
            f - blueblock)
  (:init (clear a) (clear b) (clear c)
         (clear d) (clear e) (clear f)
         (ontable a) (ontable b) (ontable c)
         (ontable d) (ontable e) (ontable f))

  (:goal (and (on a d) (on b e) (on c f)))
)
```

Example run on the FF planner

```
# ./ff -o blocks-dom.pddl -f blocks-ex.pddl
ff: parsing domain file, domain 'BLOCKS' defined
ff: parsing problem file, problem 'EXAMPLE' defined
ff: found legal plan as follows
step    0: FROMTABLE A D
        1: FROMTABLE B E
        2: FROMTABLE C F
0.01 seconds total time
```

Example: blocks world in PDDL

```
(define (domain BLOCKS)
  (:requirements :adl :typing)
  (:types block)
  (:predicates (on ?x - block ?y - block)
               (ontable ?x - block)
               (clear ?x - block)
               )
```

```
(:action fromtable
   :parameters (?x - block ?y - block)
   :precondition (and (not (= ?x ?y))
                      (clear ?x)
                      (ontable ?x)
                      (clear ?y))
   :effect
     (and (not (ontable ?x))
          (not (clear ?y))
          (on ?x ?y)))
```

```
(:action totable
   :parameters (?x - block ?y - block)
   :precondition (and (clear ?x) (on ?x ?y))
   :effect
     (and (not (on ?x ?y))
          (clear ?y)
          (ontable ?x)))
```

```
(:action move
  :parameters (?x - block
               ?y - block
               ?z - block)
  :precondition (and (clear ?x) (clear ?z)
                     (on ?x ?y) (not (= ?x ?z)))
  :effect
    (and (not (clear ?z))
         (clear ?y)
         (not (on ?x ?y))
         (on ?x ?z)))
```

```
(define (problem blocks-10-0)
  (:domain BLOCKS)
  (:objects d a h g b j e i f c - block)
  (:init (clear c) (clear f)
      (ontable i) (ontable f)
      (on c e) (on e j) (on j b) (on b g)
      (on g h) (on h a) (on a d) (on d i))
  (:goal (and (on d c) (on c f) (on f j)
              (on j e) (on e h) (on h b)
              (on b a) (on a g) (on g i)))
)
```