

Multi-Agent Systems

Albert-Ludwigs-Universität Freiburg



Bernhard Nebel, Felix Lindner, and Thorsten Engesser
Summer Term 2017

Course outline



- 1 Introduction
- 2 Agent-Based Simulation
- 3 Agent Architectures
- 4 Beliefs, Desires, Intentions
 - The GOAL Agent Programming Language
 - Introduction to Modal Logics
 - Epistemic Logic
 - Knowledge, Belief, Group knowledge
 - Dynamic Knowledge and Puzzles
 - BDI Logic
- 5 Norms and Duties
- 6 Communication and Argumentation
- 7 Coordination and Decision Making

Nebel, Lindner, Engesser – MAS

2 / 29

Recap and Overview



- Last week
 - The language of modal logics
 - Kripkean semantics for modal logics
 - Problems you are able to deal with:
 - Model Checking: Checking truth of formulas in a possible world in a Kripke model.
 - Theorem Proving: Checking validity of formulas w.r.t. a class of Kripke models.
- This week
 - The logic of knowledge (and belief)
 - Logical properties of knowledge (and belief)
 - Knowledge of groups of agents
 - Dynamics of knowledge and puzzles (Thursday)

Nebel, Lindner, Engesser – MAS

3 / 29

Motivation: Theory of Mind



- Sophisticated modes of social behavior require the ability to “put oneself in the position of someone else”
- Varieties of knowledge
 - Knowledge about others' knowledge:
 - First order: “John knows that the sun is shining”
 - Second order: “John knows that Mary knows that the sun is shining”
 - Third order: “John knows that Mary knows that Peter knows that the sun is shining”
 - ...
 - Knowledge about one's own knowledge
 - Positive introspection: “I know that I know that the sun is shining”
 - Negative introspection: “I know that I don't know that the sun is shining”

Nebel, Lindner, Engesser – MAS

4 / 29

Video: False Belief Task

- **Belief** is the attitude of assent towards the truth of particular propositions.
- **Knowledge** is true justified belief (Plato).
 - **Justification**: Evidence, or support, for your belief. I.e., if you just claim some truth without evidence, this does not count as knowledge.
- This definition is challenged by philosophical arguments (viz., by so-called **Gettier cases**).
- Standard epistemic logic is much more pragmatic, though:
≈ knowledge is true belief.

- $K_i\varphi$: Agent i **knows** φ .
- $B_i\varphi$: Agent i **believes** φ .
- Some authors also write $K(i)(p)$ or iKp resp. $B(i)(p)$ or iBp .
- One distinguishes the logic of knowledge (**epistemic logic**) from the logic of belief (**doxastic logic**). We will discuss epistemic logic and refer to doxastic logic when the distinction is interesting to us.

Def. Epistemically Accessible, Epistemic Alternative

A particular world w' is **epistemically accessible** to an agent i in world w iff the set of all propositions p that agent i knows in w are compatible with all true propositions in w' . All such worlds w' are considered **epistemic alternatives**.

Example

If Mary knows only one thing, that she exists. This means that the actual world bears the epistemic accessibility relation for Mary to any world in which she exists. All worlds in which she exists are epistemic alternatives for her.

- We also say that from what Mary knows, the epistemic alternatives are **epistemically indistinguishable** to her.

Agent i knows φ in world w iff. φ is true in all worlds w' epistemically accessible to w for i :

- $M, w \models K_i \varphi$ iff. for all w' s.th. $(w, w') \in R(K_i), M, w' \models \varphi$

Agent i believes φ in world w iff. φ is true in all worlds w' doxastically accessible to w for i :


- $M, w \models B_i \varphi$ iff. for all w' s.th. $(w, w') \in R(B_i), M, w' \models \varphi$

Additionally:

- $M, w \models \hat{K}_i \varphi$ iff. $M, w \models \neg K_i \neg \varphi$.
- $M, w \models \hat{B}_i \varphi$ iff. $M, w \models \neg B_i \neg \varphi$.

Quote [Hintikka & Halonen 98]

When you know that S, you can legitimately omit from consideration all possibilities under which it is not the case that S. In other words you can restrict your attention to the situations in which it is true that S.



- $M_1, w_1 \models \neg K_a H \wedge \neg K_a T$
- $M_2, w_1 \models K_a H$

- Some sessions ago we agreed on classifying knowledge as **S5** modality, viz.,:
 - K-axiom: $K_i(\varphi \rightarrow \psi) \rightarrow (K_i \varphi \rightarrow K_i \psi)$
 - T-axiom: $K_i \varphi \rightarrow \varphi$
 - 4-axiom: $K_i \varphi \rightarrow K_i K_i \varphi$
 - 5-axiom: $\neg K_i \varphi \rightarrow K_i \neg K_i \varphi$
- T was considered inappropriate for belief. Instead, the weaker axiom D was considered appropriate:
 - D-axiom: $B_i \varphi \rightarrow \neg B_i \neg \varphi$

$K_i(\varphi \rightarrow \psi) \rightarrow (K_i \varphi \rightarrow K_i \psi)$

- Objection: **Logical Omniscience**
 - The agent knows all implications of its knowledge.
 - The agent knows all tautologies.
- Is there a way out?
 - Not if we stick to normal modal logics. Approaches exist based on generalizations of Kripke models (impossible worlds). \Rightarrow We will not go into detail. If you are interested, see Fagin et al., 1995 [2].

Axiom T

$$K_i \varphi \rightarrow \varphi$$

- Uncontroversial for epistemic logic. Indeed, **KT** is considered weakest system for knowledge.
- $K_a K_b \varphi \models_{\mathbf{KT}} K_a \varphi$, called **transmissibility of knowledge**. You know everything you know that others know.
 - $K_a(K_b \varphi \rightarrow \varphi) \rightarrow (K_a K_b \varphi \rightarrow K_a \varphi)$ (K-Axiom)
 - $\top \rightarrow (K_a K_b \varphi \rightarrow K_a \varphi) \Rightarrow \models_{\mathbf{KT}} (K_a K_b \varphi \rightarrow K_a \varphi)$ □
- Do you also believe everything you believe that others believe? \Rightarrow Doxastic: Uncontroversial that it does not hold. Weaker axiom D instead.

Axiom D

$$K_i \varphi \rightarrow \neg K \neg \varphi$$

- Epistemic: Axiom T already entails axiom D.
- Doxastic: Considered as a substitute for T. Psychological objection: People do hold contradictory beliefs.

Axiom 4

$$K_i \varphi \rightarrow K_i K_i \varphi$$

- Doxastic: Uncontroversial.
- Epistemic:
 - Objection I: So-called *KK*-regress: Agents are required to have an infinite number of knowledge.
 - Objection IIa: A corollary of the axiom is $\neg K_i K_i \varphi \rightarrow \neg K_i \varphi$. But it seems possible to have knowledge that comes into ones mind only after one gets some hints.
 - Objection IIb: Given $K \varphi \rightarrow B \varphi$ it holds that $K \varphi \rightarrow BK \varphi$. Thus, one only knows propositions one believes to know.

However, as Hintikka notes, “Knowing to know differs only in words from knowing.” In system **KT4** we have $K_i K_i \varphi \rightarrow K_i \varphi$, $K_i \varphi \rightarrow K_i K_i \varphi$, hence $K_i K_i \varphi \leftrightarrow K_i \varphi$.

Axiom 5

$$\neg K_i \varphi \rightarrow K_i \neg K_i \varphi$$

- Objection: A corollary is $K_i \varphi \vee K_i \neg K_i \varphi$ ($\equiv_{\text{Def.}}$ awareness). No room for ignorance! Consider John living in 17th century: According to axiom 5, John either knew Einstein's theory of relativity, or he knew that he does not know Einstein's theory of relativity. In fact, it is more appropriate to claim that John was not aware.

Axiom B

From reflexivity (T) and Euclideaness (5) follows symmetry (B):

$\neg\phi \rightarrow K_i \neg K_i \phi$ (Proof: $\neg\phi \Rightarrow_T \neg K_i \phi \Rightarrow_5 K_i \neg K_i \phi$ \square)

- Objection: What is actually true must be known to be possibly true.
- Objection: A corollary of axiom B is $\neg K_i \neg K \phi \rightarrow \phi$, which is the same as $\hat{K}K\phi \rightarrow \phi$. In words: Only true things are considered possible to be known resp. believed.

As this seems too strong to most epistemologists, 5 (and thus B) is often rejected. \Rightarrow Alternative Axioms proposed: 4.2, 4.3, 4.4
However, in many computer science applications, B is considered appropriate: If the agent cannot find ϕ in its database, it can conclude that it knows that it does not know ϕ (closed-world assumption).

Axiom .4

$\phi \rightarrow (\neg K_i \neg K_i \phi \rightarrow K_i \phi)$

- A corollary is $\neg\phi \vee K_i \neg K_i \phi \vee K_i \phi$. Thus, the agent is not required to know something about things that do not obtain.
- In **KT4.4**: If ϕ is not the case, then $\neg K_i \phi$ (by T), but not $K_i \neg K_i \phi$. If ϕ is the case, then either it knows ϕ or it knows that it does not know ϕ .

Axiom .3

$K_i(K_i \phi \rightarrow K_i \psi) \vee K_i(K_i \psi \rightarrow K_i \phi)$

- Variant: $K_i(\neg K_i \phi \vee K_i \psi) \vee K_i(\neg K_i \psi \vee K_i \phi) \Rightarrow$ The agent has introspection regarding the fact that what it knows and does not know is consistent. E.g., it knows that it cannot at the same time know that ϕ and not know that ϕ .

.2

$\neg K_i \neg K_i \phi \rightarrow K_i \neg K_i \neg \phi$

- Corollary: $K_i \hat{K}_i \neg \phi \vee K_i \hat{K}_i \phi$. Agents are only required to know whether they consider some proposition or its negation possible.

Building a logic with both these modalities interacting is non-trivial. Consider:

- **Entailment property:** $K_i \varphi \rightarrow B_i \varphi$
- **Positive certainty property:** $B_i \varphi \rightarrow B_i K_i \varphi$
- And let B be a **KD45** modality and K a **S5** modality. Then $\neg B_i \varphi \rightarrow B_i \neg K_i \varphi$ holds:
 - $\neg B_i \varphi \Rightarrow_{\text{Entailment}} \neg K_i \varphi \Rightarrow_5 K_i \neg K_i \varphi \Rightarrow_{\text{Entailment}} B_i \neg K_i \varphi \quad \square$
- **Objection**
 - Let p be a proposition the agent believes, but in fact p is false: $B_i p \wedge \neg p$
 - $\Rightarrow_{\text{Positive Certainty}} B_i K_i p$
 - $\Rightarrow_{\text{T}} \neg K_i p \Rightarrow_5 K_i \neg K_i p \Rightarrow_{\text{Entailment}} B_i \neg K_i p \quad \nabla$

- Extend language by three modal operators:
 - $E_G \varphi$: **Everyone** in the group G **knows** φ .
 - $C_G \varphi$: It is **common knowledge** among the agents in G that φ is the case.
 - $D_G \varphi$: It is **distributed knowledge** among the agents in G that φ is the case.
- **Example**
 - $K_3 C_{\{1,2\}} p$: Agent 3 knows that it is common knowledge among agents 1 and 2 that p is the case.

- $M, w \models E_G \varphi$ iff. $M, w \models K_i \varphi$ for all $i \in G$.
- Write $E_G^0 \varphi$ as an abbreviation of φ , $E_G^1 \varphi$ as an abbreviation for $K_1 \varphi \wedge K_1 \varphi \wedge \dots$, and let $E_G^{k+1} \varphi$ be an abbreviation for $E_G E_G^k \varphi$.

Def. G-reachable in k steps

A world w' is **G-reachable** from world w in $k \geq 1$ steps iff. there exists worlds $u_0 u_1 \dots u_k$ such that $u_0 = w$ and $u_k = w'$ and for all j with $0 \leq j \leq k-1$ there exists $i \in G$ s.th. $(s_j, s_{j+1}) \in R(K_i)$.

Lemma

$M, w \models E_G^k \varphi$ iff. $M, w' \models \varphi$ for all w' that are G -reachable from w in k steps.

- $M, w \models C_G \varphi$ iff. $M, w \models E_G^k \varphi$ for $k = 1, 2, \dots$

Def. G-reachable

A world w' is **G-reachable** from world w iff. w' is G -reachable from w in k steps for some $k \geq 1$.

Lemma


$M, w \models C_G \varphi$ iff. $M, w' \models \varphi$ for all w' that are G -reachable from w .

Distributed Knowledge

A group of agents G has **distributed knowledge** of φ iff the combined knowledge of the members of G implies φ . Idea: Eliminate all worlds that some agent in G considers impossible. Technically: Intersect the sets of worlds each agent in G considers possible. Hence:


- $M, w \models D_G \varphi$ iff. $M, w' \models \varphi$ for all w' s.th. $(w, w') \in \bigcap_{i \in G} K_i$

- First, it is common knowledge that the ball is in the box



$$M_1, w_1 \models E_{\{1,2\}} b \wedge C_{\{1,2\}} b \wedge D_{\{1,2\}} b$$


- Afterwards, the ball is not in the box. A knows, B does not.



$$M_2, w_2 \models \neg E_{\{1,2\}} \neg b \wedge \neg C_{\{1,2\}} \neg b \wedge D_{\{1,2\}} \neg b$$

- Today
 - Critical discussion of the formal properties of knowledge and belief as modeled in modal logics. **S5** seems to be quasi-standard model for knowledge in computer science, there may be good reasons to make other choices for your purpose.
 - Foundations of group knowledge: Everyone knows, Common knowledge, and distributed knowledge.
- Next time: Dynamics and Puzzles

- 1 Introduction
- 2 Agent-Based Simulation
- 3 Agent Architectures
- 4 Beliefs, Desires, Intentions
 - The GOAL Agent Programming Language
 - Introduction to Modal Logics
 - Epistemic Logic
 - Knowledge, Belief, Group knowledge
 - Dynamic Knowledge and Puzzles
 - BDI Logic
- 5 Norms and Duties
- 6 Communication and Argumentation
- 7 Coordination and Decision Making

-  J. Garson, 2004, <https://plato.stanford.edu/entries/logic-modal/>
-  R. Fagin, J. Y. Halpern, Y. Moses, M. Y. Vardi, Reasoning about knowledge, The MIT Press, 1995.
-  J. Symons, Logic and formal semantics for epistemology, in The Routledge Companion to Epistemology (Routledge Philosophy Companions) Duncan Pritchard and Sven Bernecker (eds.), New York: Routledge. 571–586, 2011.