

Principles of AI Planning

Prof. Dr. B. Nebel, Dr. R. Mattmüller
 D. Speck
 Winter Semester 2014/2015


University of Freiburg
 Department of Computer Science

Exercise Sheet 9

Due: Friday, January 9th, 2015

Exercise 9.1 (Additive patterns and canonical heuristic, 2+2+1 points)

Consider the Sokoban problem given by the picture below. The red circle denotes the agent's position, the blue squares are boxes, and the green grid cells are the target positions of the boxes (it is irrelevant which box ends up in which target position). The letters only denote the names of the grid cells.



We will model this problem in finite-domain representation using the variables $position_p$, $position_{s_1}$, $position_{s_2}$, $at-goal_{s_1}$, $at-goal_{s_2}$, $content_A$, $content_B, \dots, content_T$ with the following domains:

- $\mathcal{D}_{position_p} = \mathcal{D}_{position_{s_1}} = \mathcal{D}_{position_{s_2}} = \{A, B, \dots, T\}$
- $\mathcal{D}_{at-goal_{s_1}} = \mathcal{D}_{at-goal_{s_2}} = \{\text{true}, \text{false}\}$
- $\mathcal{D}_{content_A} = \dots = \mathcal{D}_{content_T} = \{\text{nothing}, p, s_1, s_2\}$

The initial state is given as

- $position_p = S, position_{s_1} = M, position_{s_2} = H, at-goal_{s_1} = at-goal_{s_2} = \text{false}$
- $content_H = s_2, content_M = s_1, content_S = p$
- $content_X = \text{nothing}$ for $X \in \{A, \dots, T\} \setminus \{H, M, S\}$

and the goal formula is $at-goal_{s_1} = \text{true} \wedge at-goal_{s_2} = \text{true}$. The set of available operators contains the obvious FDR formalizations of all *move*- and *push*-actions that are usually available in Sokoban.

Consider the pattern collection \mathcal{C} with the following patterns:

- $P_1 = \{at-goal_{s_2}\}$
- $P_2 = \{at-goal_{s_1}, position_{s_1}\}$
- $P_3 = \{at-goal_{s_2}, position_{s_2}\}$
- $P_4 = \{at-goal_{s_1}, position_{s_1}, position_p\}$
- $P_5 = \{position_{s_1}, position_p\}$
- $P_6 = \{at-goal_{s_1}, content_H\}$
- $P_7 = \{at-goal_{s_1}, content_G\}$
- $P_8 = \{at-goal_{s_2}, content_D\}$
- $P_9 = \{content_A, content_E\}$
- $P_{10} = \{at-goal_{s_1}, content_Q\}$

- (a) Specify the compatibility graph of \mathcal{C} and determine its maximal cliques.
- (b) Determine the canonical heuristic $h^{\mathcal{C}}$ and simplify it as much as possible.
- (c) Not all patterns in \mathcal{C} are reasonable. Which can obviously be omitted, and why? What would the canonical heuristic look like if we omitted those patterns before even constructing the compatibility graph?

Exercise 9.2 (Pattern selection, 5 points)

Consider an SAS⁺-planning task $\Pi = \langle V, I, O, \gamma \rangle$. Let $P \subset V$ be a pattern such that all variables in P are causally relevant in P and that P is causally connected. Let $v \in V \setminus P$ and $P' = P \cup \{v\}$. Show that the following two statements are equivalent:

- (a) All variables in P' are causally relevant in P' and P' is causally connected.
- (b) Variable v is a predecessor of some $u \in P$ in $\text{CG}(\Pi)$, or v is a successor of some $u \in P$ in $\text{CG}(\Pi)$ and is mentioned in γ .

You can and should solve the exercise sheets in groups of two. Please state both names on your solution.