# REIBURG

# Principles of AI Planning

3. Normal forms

Albert-Ludwigs-Universität Freiburg

Bernhard Nebel and Robert Mattmüller October 19th, 2018

#### Motivation



Similarly to normal forms in propositional logic (DNF, CNF, NNF, ...) we can define normal forms for effects, operators and planning tasks.

This is useful because algorithms (and proofs) then only need to deal with effects (resp. operators or tasks) in normal form.

#### Motivation

Effect normal form

Positive normal form

011111 0



#### Motivation

## Effect normal form

Definition Example

Positive normal form

STRIPS

Summary

# Effect normal form



#### Definition (equivalent effects)

Two effects e and e' over state variables A are equivalent, written  $e \equiv e'$ , if for all states s over A,  $[e]_s = [e']_s$ .

## Definition (equivalent operators)

Two operators o and o' over state variables A are equivalent, written  $o \equiv o'$ , if they are applicable in the same states, and for all states s where they are applicable,  $app_o(s) = app_{o'}(s)$ .

#### **Theorem**

Let  $o = \langle \chi, e \rangle$  and  $o' = \langle \chi', e' \rangle$  be operators with  $\chi \equiv \chi'$  and  $e \equiv e'$ . Then  $o \equiv o'$ .

Note: The converse is not true. (Why not?)

Motivation

Effect normal form

Definition

Positive

STRIPS

# Equivalence transformations for effects



# FREB

$$e_1 \wedge e_2 \equiv e_2 \wedge e_1 \tag{1}$$

$$(e_1 \wedge e_2) \wedge e_3 \equiv e_1 \wedge (e_2 \wedge e_3)$$
 (2)

$$\top \wedge e \equiv e$$

$$\chi \rhd e \equiv \chi' \rhd e \quad \text{if } \chi \equiv \chi'$$

$$\top \triangleright e \equiv e$$

$$\bot \triangleright e \equiv \top$$

$$\chi_1 \rhd (\chi_2 \rhd e) \equiv (\chi_1 \land \chi_2) \rhd e$$

$$\chi \rhd (e_1 \wedge \cdots \wedge e_n) \equiv (\chi \rhd e_1) \wedge \cdots \wedge (\chi \rhd e_n) \qquad (8)$$

$$(\chi_1 \rhd e) \land (\chi_2 \rhd e) \equiv (\chi_1 \lor \chi_2) \rhd e \tag{9}$$

#### Motivation

Effect normal

Equivalences Definition

Example

normal form

STRIPS

Summary

(3)

(4)

(5)

(6)

(7)

#### Normal form for effects



We can define a normal form for effects:

- Nesting of conditionals, as in  $a \triangleright (b \triangleright c)$ , can be eliminated.
- Effects e within a conditional effect  $\varphi \triangleright e$  can be restricted to atomic effects (e or  $\neg a$ ).

Transformation to this effect normal form only gives a small polynomial size increase.

Compare: transformation to CNF or DNF may increase formula size exponentially.

Motivation

Effect norma form

Definition

Positive normal form

STRIPS





#### Definition

An operator  $\langle \chi, e \rangle$  is in effect normal form (ENF) if for all occurrences of  $\chi' \rhd e'$  in e the effect e' is either a or  $\neg a$  for some  $a \in A$ , and there is at most one occurrence of any atomic effect in e.

#### **Theorem**

For every operator there is an equivalent one in effect normal form.

Proof is constructive: we can transform any operator into effect normal form using the equivalence transformations for effects.

Motivation

form

Definition

Example

normal form

\_

# Effect normal form example



# UNI FREIB

#### Example

$$(a\rhd (b\land (c\rhd (\neg d\land e))))\land (\neg b\rhd e)$$

transformed to effect normal form is

$$(a \triangleright b) \land ((a \land c) \triangleright \neg d) \land ((\neg b \lor (a \land c)) \triangleright e)$$

#### Motivation

Effect normal form

Definition

Example

Positive normal form

STRIFS



# Positive normal form

#### Motivation

Effect normal form

#### Positive normal form

Definition & algorithm Example

Exampl Advanta

STRIPS

# **Example: Freecell**





#### Motivation

Effect normal

Positive

Motivation

Advantage

Summary

#### Example (good and bad effects)

If we move a card c to a free tableau position, the good effect is that the card formerly below c is now available.

The bad effect is that we lose one free tableau position.

# What is a good or bad effect?



Question: Which operator effects are good, and which are bad?

Difficult to answer in general, because it depends on context:

- Locking the entrance door is good if we want to keep burglars out.
- Locking the entrance door is bad if we want to enter.

We will now consider a reformulation of planning tasks that makes the distinction between good and bad effects obvious.

Motivatio

Effect normal form

Positive normal forn

normal form

Definition & algorithm

Advantage

STRIPS



# . . . . . .

## Definition (operators in positive normal form)

An operator  $o = \langle \chi, e \rangle$  is in positive normal form if it is in effect normal form, no negation symbols appear in  $\chi$ , and no negation symbols appear in any effect condition in e.

## Definition (planning tasks in positive normal form)

A planning task  $\langle A, I, O, \gamma \rangle$  is in positive normal form if all operators in O are in positive normal form and no negation symbols occur in the goal  $\gamma$ .

Motivation

Effect norma form

Positive normal form

Definition & algorithm

Example Advantage

STRIPS



# FREIB

## Theorem (positive normal form)

Every planning task  $\Pi$  has an equivalent planning task  $\Pi'$  in positive normal form.

Moreover,  $\Pi'$  can be computed from  $\Pi$  in polynomial time.

Note: Equivalence here means that the represented transition systems of  $\Pi$  and  $\Pi'$ , limited to the states that can be reached from the initial state, are isomorphic.

We prove the theorem by describing a suitable algorithm. (However, we do not prove its correctness or complexity.)

Motivation

Effect normal form

Positive normal form

Definition & algorithm

Advantage

STRIPS



SH -

## Transformation of $\langle A, I, O, \gamma \rangle$ to positive normal form

Convert all operators  $o \in O$  to effect normal form.

Convert all conditions to negation normal form (NNF).

**while** any condition contains a negative literal  $\neg a$ :

Let a be a variable which occurs negatively in a condition.

 $A := A \cup \{\hat{a}\}\$ for some new state variable  $\hat{a}$ 

 $I(\hat{a}) := 1 - I(a)$ 

Replace the effect a by  $(a \land \neg \hat{a})$  in all operators  $o \in O$ .

Replace the effect  $\neg a$  by  $(\neg a \land \hat{a})$  in all operators  $o \in O$ .

Replace  $\neg a$  by  $\hat{a}$  in all conditions.

Convert all operators  $o \in O$  to effect normal form (again).

Here, *all conditions* refers to all operator preconditions, operator effect conditions and the goal.

Motivation

Effect norma form

Positive normal form

Definition & algorithm

Advantage

TRIPS





#### Example (transformation to positive normal form)

```
A = \{home, uni, lecture, bike, bike-locked\}
I = \{home \mapsto 1, bike \mapsto 1, bike-locked \mapsto 1, \\ uni \mapsto 0, lecture \mapsto 0\}
O = \{\langle home \land bike \land \neg bike-locked, \neg home \land uni \rangle, \\ \langle bike \land bike-locked, \neg bike-locked \rangle, \\ \langle bike \land \neg bike-locked, bike-locked \rangle, \\ \langle uni, lecture \land ((bike \land \neg bike-locked) \rhd \neg bike) \rangle\}
\gamma = lecture \land bike
```

#### Motivation

Effect normal form

Positive

normal form

algorithm Example

Example Advantage

TRIPS



# ZE ZE

## Example (transformation to positive normal form)

```
A = \{home, uni, lecture, bike, bike-locked\}
I = \{home \mapsto 1, bike \mapsto 1, bike-locked \mapsto 1, \\ uni \mapsto 0, lecture \mapsto 0\}
O = \{\langle home \land bike \land \neg bike-locked, \neg home \land uni \rangle, \\ \langle bike \land bike-locked, \neg bike-locked \rangle, \\ \langle bike \land \neg bike-locked, bike-locked \rangle, \\ \langle uni, lecture \land ((bike \land \neg bike-locked) \rhd \neg bike) \rangle\}
\gamma = lecture \land bike
```

Identify state variable a occurring negatively in conditions.

Motivation

Effect normal form

Positive

normal form

lgorithm

Example Advantage

TDIDE



# Example (transformation to positive normal form)

```
A = \{home, uni, lecture, bike, bike-locked, bike-unlocked\}
I = \{home \mapsto 1, bike \mapsto 1, bike-locked \mapsto 1,
uni \mapsto 0, lecture \mapsto 0, bike-unlocked \mapsto 0\}
O = \{\langle home \land bike \land \neg bike-locked, \neg home \land uni \rangle,
\langle bike \land bike-locked, \neg bike-locked \rangle,
\langle bike \land \neg bike-locked, bike-locked \rangle,
\langle uni, lecture \land ((bike \land \neg bike-locked) \rhd \neg bike) \rangle\}
\gamma = lecture \land bike
```

Introduce new variable â with complementary initial value.

Motivation

Effect normal

Positive

normal form

Definition 8 algorithm Example

Advantage

TRIPS





## Example (transformation to positive normal form)

```
A = \{home, uni, lecture, bike, bike-locked, bike-unlocked\}
I = \{home \mapsto 1, bike \mapsto 1, bike-locked \mapsto 1,
uni \mapsto 0, lecture \mapsto 0, bike-unlocked \mapsto 0\}
O = \{\langle home \land bike \land \neg bike-locked, \neg home \land uni \rangle,
\langle bike \land bike-locked, \neg bike-locked \rangle,
\langle bike \land \neg bike-locked, bike-locked \rangle,
\langle uni, lecture \land ((bike \land \neg bike-locked) \rhd \neg bike) \rangle\}
\gamma = lecture \land bike
```

#### Identify effects on variable a.

Motivation

Effect normal form

Positive

normal form

algorithm Example

Advantage

TRIPS



# FREIB

## Example (transformation to positive normal form)

```
A = \{home, uni, lecture, bike, bike-locked, bike-unlocked\}
I = \{home \mapsto 1, bike \mapsto 1, bike-locked \mapsto 1,
uni \mapsto 0, lecture \mapsto 0, bike-unlocked \mapsto 0\}
O = \{\langle home \land bike \land \neg bike-locked, \neg home \land uni \rangle,
\langle bike \land bike-locked, \neg bike-locked \land bike-unlocked \rangle,
\langle bike \land \neg bike-locked, bike-locked \land \neg bike-unlocked \rangle,
\langle uni, lecture \land ((bike \land \neg bike-locked) \rhd \neg bike) \rangle\}
\gamma = lecture \land bike
```

## Introduce complementary effects for â.

Motivation

Effect normal form

Positive

normal forn

algorithm Example

Example Advantage

TRIPS



# Example (transformation to positive normal form)

```
A = \{home, uni, lecture, bike, bike-locked, bike-unlocked\}
I = \{home \mapsto 1, bike \mapsto 1, bike-locked \mapsto 1, \\ uni \mapsto 0, lecture \mapsto 0, bike-unlocked \mapsto 0\}
O = \{\langle home \land bike \land \neg bike-locked, \neg home \land uni \rangle, \\ \langle bike \land bike-locked, \neg bike-locked \land bike-unlocked \rangle, \\ \langle bike \land \neg bike-locked, bike-locked \land \neg bike-unlocked \rangle, \\ \langle uni, lecture \land ((bike \land \neg bike-locked) \rhd \neg bike) \rangle\}
\gamma = lecture \land bike
```

Identify negative conditions for a.

Motivation

Effect normal

Positive

normal form

algorithm

Example

Advantage

TRIPS





## Example (transformation to positive normal form)

```
A = \{home, uni, lecture, bike, bike-locked, bike-unlocked\}
I = \{home \mapsto 1, bike \mapsto 1, bike-locked \mapsto 1, \\ uni \mapsto 0, lecture \mapsto 0, bike-unlocked \mapsto 0\}
O = \{\langle home \land bike \land bike-unlocked, \neg home \land uni \rangle, \\ \langle bike \land bike-locked, \neg bike-locked \land bike-unlocked \rangle, \\ \langle bike \land bike-unlocked, bike-locked \land \neg bike-unlocked \rangle, \\ \langle uni, lecture \land ((bike \land bike-unlocked) \rhd \neg bike) \rangle\}
\gamma = lecture \land bike
```

#### Replace by positive condition â.

Motivation

Effect normal

Positive

normal form

algorithm Example

Advantage

TRIPS





## Example (transformation to positive normal form)

```
A = \{home, uni, lecture, bike, bike-locked, bike-unlocked\}
I = \{home \mapsto 1, bike \mapsto 1, bike-locked \mapsto 1, \\ uni \mapsto 0, lecture \mapsto 0, bike-unlocked \mapsto 0\}
O = \{\langle home \land bike \land bike-unlocked, \neg home \land uni \rangle, \\ \langle bike \land bike-locked, \neg bike-locked \land bike-unlocked \rangle, \\ \langle bike \land bike-unlocked, bike-locked \land \neg bike-unlocked \rangle, \\ \langle uni, lecture \land ((bike \land bike-unlocked) \rhd \neg bike) \rangle\}
\gamma = lecture \land bike
```

#### Motivation

Effect normal

Positive

Motivation Definition &

Example

Advantage

TRIPS

# Why positive normal form is interesting



In positive normal form, good and bad effects are easy to distinguish:

- Effects that make state variables true are good (add effects).
- Effects that make state variables false are bad (delete effects).

This is of high relevance for some planning techniques that we will see later in this course.

Motivation

Effect normal form

Positive

normal for

Definition & algorithm

Advantage

STRIPS



# STRIPS operators

Motivation

Effect normal form

Positive normal form

#### STRIPS Definition

Propertie

#### Definition

An operator  $\langle \chi, e \rangle$  is a STRIPS operator if

- $\mathbf{x}$  is a conjunction of atoms, and
- e is a conjunction of atomic effects.

Hence every STRIPS operator is of the form

$$\langle a_1 \wedge \cdots \wedge a_n, I_1 \wedge \cdots \wedge I_m \rangle$$

where  $a_i$  are atoms and  $l_j$  are atomic effects.

Note: Sometimes we allow conjunctions of literals as preconditions. We denote this as STRIPS with negative preconditions.

Motivation

Effect normal form

Positive normal form

Definition

Properties

# Why STRIPS is interesting



- STRIPS operators are particularly simple, yet expressive enough to capture general planning problems.
- In particular, STRIPS planning is no easier than general planning problems.
- Many algorithms in the planning literature are only presented for STRIPS operators (generalization is often, but not always, obvious).

#### Motivation

Effect normal form

Positive normal form

Definition

Properties

lummary

#### **STRIPS**

STanford Research Institute Planning System (Fikes & Nilsson, 1971)

#### Transformation to STRIPS



- Not every operator is equivalent to a STRIPS operator.
- However, each operator can be transformed into a set of STRIPS operators whose "combination" is equivalent to the original operator. (How?)
- However, this transformation may exponentially increase the number of required operators. There are planning tasks for which such a blow-up is unavoidable.
- There are polynomial transformations of planning tasks to STRIPS, but these do not preserve the structure of the transition system (e.g., length of shortest plans may change).

Motivation

Effect normal form

Positive normal form

Definition

Properties

Positive normal form

OTTIN O

- Effect normal form simplifies structure of operator effects: conditional effects contain only atomic effects; there is at most one occurrence of any atomic effect.
- Positive normal form allows to distinguish good and bad effects.
- The form of STRIPS operators is even more restrictive than effect normal form, forbidding complex preconditions and conditional effects.
- All three forms are expressive enough to capture general planning problems.
- Transformation to effect normal form and positive normal form possible with polynomial size increase.
- Structure preserving transformations of planning tasks to STRIPS can increase the number of operators exponentially.